

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 1/11  
(30779527/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## 60U-05 Catalyst

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
5025 Creekbank Road  
Building A, Floor 2  
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Acute Tox.	3 (dermal)	Acute toxicity
Acute Tox.	3 (Inhalation - vapour)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27

Version: 6.1

Page: 2/11

(30779527/SDS\_GEN\_CA/EN)

Repr.	1 (unborn child)	Reproductive toxicity
Repr.	1 (fertility)	Reproductive toxicity
STOT RE	1	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Muta.	2	Germ cell mutagenicity
STOT SE	1	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H341	Suspected of causing genetic defects.
H360	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H412	Harmful to aquatic life with long lasting effects.
H372	Causes damage to organs (Immune system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P270	Do not eat, drink or smoke when using this product.
P260	Do not breathe dust or mist.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.

Precautionary Statements (Response):

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27

Version: 6.1

Page: 3/11

(30779527/SDS\_GEN\_CA/EN)

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or physician.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P330	Rinse mouth
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P308 + P313	IF exposed or concerned: Get medical attention.
P314	Get medical advice/attention if you feel unwell.
P311	Call a POISON CENTER or physician.

### Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

### Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

## Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

dibutyltin dilaurate

CAS Number: 77-58-7

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: Dibutylbis[1-oxododecyl]oxy]stannane; Dibutyltin dilaurate

2,4-pentanedione

CAS Number: 123-54-6

Content (W/W):  $\geq 75.0$  -  $\leq 100.0\%$

Synonym: Acetylacetone

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 4/11  
(30779527/SDS\_GEN\_CA/EN)

### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

## Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: dibutyltin dilaurate*

*Symptoms: Overexposure may cause:, unconsciousness, vomiting, abdominal cramps, dyspnea, diarrhea, coughing*

*Information on: 2,4-pentanedione*

*Symptoms: Overexposure may cause:, unconsciousness, vomiting, nausea, headache, dizziness*  
-----

## Indication of any immediate medical attention and special treatment needed

### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 5/11  
(30779527/SDS\_GEN\_CA/EN)

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27

Version: 6.1

Page: 6/11

(30779527/SDS\_GEN\_CA/EN)

dibutyltin dilaurate	ACGIH, US:	TWA value 0.1 mg/m3 (tin (Sn));
	ACGIH, US:	STEL value 0.2 mg/m3 (tin (Sn));
	OSHA Z1:	PEL 0.1 mg/m3 (tin (Sn));
	ACGIH, US:	Skin Designation (tin (Sn)); Danger of cutaneous absorption
2,4-pentanedione	ACGIH, US:	TWA value 25 ppm ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:	No applicable information available.	
Colour:	No applicable information available.	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	140.00 - 204.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	32.78 °C	(ASTM D3278)
Flammability:	No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27

Version: 6.1

Page: 7/11

(30779527/SDS\_GEN\_CA/EN)

Vapour pressure:	6.86 mmHg ( 20 °C)	
Density:	0.9799 g/cm3 ( 20 °C)	(calculated)
Relative density:	0.9800 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.600 mm2/s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

Thermal decomposition:  
No applicable information available.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation. Of pronounced toxicity after short-term skin contact.

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 8/11  
(30779527/SDS\_GEN\_CA/EN)

*Information on: dibutyltin dilaurate*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic after a single skin contact.*

*Information on: 2,4-pentanedione*

*Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term skin contact. Of pronounced toxicity after short-term inhalation.*

### Oral

Type of value: LD50

Species: rat

Value:  $\geq 570.00000$  mg/kg

### Inhalation

Type of value: LC50

Species: rat

Value:  $5,104.000000$  mg/l

### Dermal

Type of value: LD50

Species: rabbit

Value:  $\geq 790.00000$  mg/kg

### Assessment other acute effects

Assessment of STOT single:

A single exposure may have relevant toxic effects on organs.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

*Information on: dibutyltin dilaurate*

*Assessment of irritating effects: Corrosive! Damages skin and eyes.*

### Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

*Information on: dibutyltin dilaurate*

*Assessment of sensitization:*

*Sensitization after skin contact possible.*

*Information on: 2,4-pentanedione*

*Assessment of sensitization:*

*The chemical structure suggests a sensitizing effect.*

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.



# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 9/11  
(30779527/SDS\_GEN\_CA/EN)

*Information on: dibutyltin dilaurate*

*Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.*

*Information on: 2,4-pentanedione*

*Assessment of repeated dose toxicity: Repeated inhalation exposure to large quantities may affect certain organs. Damages the central nerve system.*

### Genetic toxicity

Assessment of mutagenicity: Mutagenic properties can not be excluded on the basis of experimental data.

*Information on: dibutyltin dilaurate*

*Assessment of mutagenicity: Mutagenic properties can not be excluded on the basis of experimental data.*

### Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

### Reproductive toxicity

Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals.

*Information on: dibutyltin dilaurate*

*Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### Teratogenicity

Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals.

*Information on: dibutyltin dilaurate*

*Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals.*

*Information on: 2,4-pentanedione*

*Assessment of teratogenicity: The substance did not cause malformations in animal studies. When given in high doses fetotoxicity was observed.*

*The substance did not cause malformations in animal studies; however, toxicity to development was observed at doses that were toxic to the parental animals.*

---

## 12. Ecological Information

### **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 10/11  
(30779527/SDS\_GEN\_CA/EN)

### Additional information

Other ecotoxicological advice:  
Acutely toxic for aquatic organisms.

## 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

### Container disposal:

WARNING: Empty containers may still contain hazardous residue.

## 14. Transport Information

### Land transport

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 2310
Hazard label:	3, 6.1
Proper shipping name:	PENTANE-2,4-DIONE

### Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 2310
Hazard label:	3, 6.1
Marine pollutant:	NO
Proper shipping name:	PENTANE-2,4-DIONE

### Air transport

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 2310
Hazard label:	3, 6.1
Proper shipping name:	PENTANE-2,4-DIONE

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical          DSL, CA          released / listed

# Safety Data Sheet

## 60U-05 Catalyst

Revision date : 2022/04/27  
Version: 6.1

Page: 11/11  
(30779527/SDS\_GEN\_CA/EN)

---

**NFPA Hazard codes:**

Health: 3      Fire: 3      Reactivity: 0      Special:

---

### 16. Other Information

**SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2022/04/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET