



We create chemistry

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05
Version: 7.0

Page: 1/9
(30778988/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

70U-10 WB AllPurpseCleanr

Recommended use of the chemical and restriction on use

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Eye Dam./Irrit.

2A

Serious eye damage/eye irritation

Flam. Liq.

2

Flammable liquids

Label elements

Pictogram:

Safety Data Sheet

70U-10 WB AllPurposeCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 2/9

(30778988/SDS_GEN_CA/EN)



Signal Word:
Danger

Hazard Statement:

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary Statements (Prevention):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves, protective clothing and eye protection or face protection.
P240 Ground and bond container and receiving equipment.
P233 Keep container tightly closed.
P243 Take action to prevent static discharges.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use only non-sparking tools.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical attention.
P370 + P378 In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Acetone

CAS Number: 67-64-1
Content (W/W): ≥ 7.0 - $< 10.0\%$
Synonym: Acetone

Ethanol, 2-propoxy-

CAS Number: 2807-30-9
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: 2-Propoxyethanol

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05
Version: 7.0

Page: 3/9
(30778988/SDS_GEN_CA/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

If irritation develops, seek medical attention. Wash affected areas with water for at least 15 minutes.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Ethanol, 2-propoxy-

Symptoms: Overexposure may cause: corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 4/9

(30778988/SDS_GEN_CA/EN)

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), Stove-lacquer KNS L-5X, Stove-lacquer Valspar HXR008F red, HDPE fluorinated

Further information on storage conditions: Keep container tightly closed. Store protected against freezing. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 5/9

(30778988/SDS_GEN_CA/EN)

Protect from temperatures above: 49 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Acetone	ACGIH, US:	TWA value 250 ppm ;
	ACGIH, US:	STEL value 500 ppm ;
	OSHA Z1:	PEL 1,000 ppm 2,400 mg/m3 ;

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid
Odour:	No data available.
Odour threshold:	No applicable information available.
Colour:	clear
pH value:	No applicable information available.
Melting point:	No applicable information available.
Freezing point:	No applicable information available.
Boiling range:	56.00 - 149.50 °C
Sublimation point:	No applicable information available.
Flash point:	17.50 °C
Flammability:	No applicable information available.
Lower explosion limit:	1.30 %(V)
Upper explosion limit:	15.80 %(V)
Autoignition:	No applicable information available.
Vapour pressure:	33.08 mmHg (20 °C)

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 6/9

(30778988/SDS_GEN_CA/EN)

Density:	0.9763 g/cm3 (20 °C)	(calculated)
Relative density:	0.9763 (20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	5.100 mm2/s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:
carbon dioxide, carbon monoxide

Thermal decomposition:
No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Information on: Acetone

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05

Page: 7/9

Version: 7.0

(30778988/SDS_GEN_CA/EN)

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. High concentrations in the air may cause narcosis.

Information on: Ethanol, 2-propoxy-

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Virtually nontoxic by inhalation. Of moderate toxicity after short-term skin contact.

Oral

No applicable information available.

Type of value: LD50

Species: rat

Value: 3,089.000000 mg/kg

Inhalation

No applicable information available.

Type of value: LC50

Species: rat

Value: 76.000000 mg/l

Dermal

No applicable information available.

Type of value: LD50

Species: rabbit

Value: 1,337.000000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

Information on: Acetone

Assessment of irritating effects: Irritating to eyes. Not irritating to the skin. Repeated exposure may cause skin dryness or cracking.

Information on: Ethanol, 2-propoxy-

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

70U-10 WB AllPurpseCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 8/9

(30778988/SDS_GEN_CA/EN)

Information on: Acetone

Assessment of repeated dose toxicity: The substance may cause damage to the testes after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the hematological system after repeated ingestion of high doses. The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Information on: Acetone

Assessment of reproduction toxicity: As shown in animal studies, the product may cause damage to the testes after repeated high exposures that cause other toxic effects.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways.

Based on available data, the classification criteria are not met.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Container disposal:

WARNING: Empty containers may still contain hazardous residue.

14. Transport Information

Land transport

TDG

Hazard class: 3

Packing group: II

ID number: UN 1263

Hazard label: 3

Safety Data Sheet

70U-10 WB AllPurposeCleanr

Revision date : 2022/03/05

Version: 7.0

Page: 9/9

(30778988/SDS_GEN_CA/EN)

Proper shipping name: PAINT RELATED MATERIAL

Sea transport

IMDG

Hazard class: 3
Packing group: II
ID number: UN 1263
Hazard label: 3
Marine pollutant: NO
Proper shipping name: PAINT RELATED MATERIAL

Air transport

IATA/ICAO

Hazard class: 3
Packing group: II
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT RELATED MATERIAL

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2022/03/05

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET