



We create chemistry

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 1/17
(30786079/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

65U-10 Clearcoat Blender

Recommended use of the chemical and restriction on use

Recommended use*: Paints, Coatings and Related Materials; for industrial use only
Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Substance number: 156271
Chemical family: Coating

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 2/17
(30786079/SDS_GEN_CA/EN)

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Flam. Aerosol	1	Flammable aerosols
STOT RE	2	Specific target organ toxicity — repeated exposure
Press. Gas	Liquef. Gas	Gases under pressure
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements (Prevention):

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08

Version: 7.0

Page: 3/17

(30786079/SDS_GEN_CA/EN)

P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P260	Do not breathe dust or mist.
P211	Do not spray on an open flame or other ignition source.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated body parts thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection or face protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P405	Store locked up.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No applicable information available.

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08

Version: 7.0

Page: 4/17

(30786079/SDS_GEN_CA/EN)

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

1-methoxy-2-propylacetate

CAS Number: 108-65-6

Content (W/W): ≥ 7.0 - $< 10.0\%$

Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

cyclohexanone

CAS Number: 108-94-1

Content (W/W): ≥ 7.0 - $< 10.0\%$

Synonym: No data available.

n-Butyl acetate

CAS Number: 123-86-4

Content (W/W): ≥ 5.0 - $< 7.0\%$

Synonym: n-Butyl acetate

ethyl acetate

CAS Number: 141-78-6

Content (W/W): ≥ 5.0 - $< 7.0\%$

Synonym: Acetic acid, ethyl ester

pentyl acetate

CAS Number: 628-63-7

Content (W/W): ≥ 1.0 - $< 3.0\%$

Synonym: Amyl acetate

Xylene

CAS Number: 1330-20-7

Content (W/W): ≥ 5.0 - $< 7.0\%$

Synonym: Xylene; Dimethylbenzene

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 5/17
(30786079/SDS_GEN_CA/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: cyclohexanone

Symptoms: Overexposure may cause:, unconsciousness, headache

Information on: ethyl acetate

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 6/17
(30786079/SDS_GEN_CA/EN)

Information on: pentyl acetate
Symptoms: No data available.

Information on: Xylene
Symptoms: Overexposure may cause: coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released. Aerosol container contains flammable gas under pressure.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 7/17
(30786079/SDS_GEN_CA/EN)

water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Do not expose to temperatures exceeding 50°C/ 122°F. Segregate from strong acids.

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 8/17
(30786079/SDS_GEN_CA/EN)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:
Consult local fire marshal for storage requirements.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

cyclohexanone	OSHA PEL	PEL 50 ppm 200 mg/m3 ; TWA value 25 ppm 100 mg/m3 ; SKIN_FINAL ; The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 20 ppm ; STEL value 50 ppm ; Skin Designation ; Danger of cutaneous absorption Skin Designation ; Danger of cutaneous absorption
n-Butyl acetate	OSHA PEL	PEL 150 ppm 710 mg/m3 ; STEL value 200 ppm 950 mg/m3 ; TWA value 150 ppm 710 mg/m3 ;
	ACGIH TLV	STEL value 150 ppm ; TWA value 50 ppm ;
ethyl acetate	OSHA PEL	PEL 400 ppm 1,400 mg/m3 ; TWA value 400 ppm 1,400 mg/m3 ;
	ACGIH TLV	TWA value 400 ppm ;
pentyl acetate	OSHA PEL	PEL 100 ppm 525 mg/m3 ; TWA value 100 ppm 525 mg/m3 ;
	ACGIH TLV	TWA value 50 ppm ; STEL value 100 ppm ;
Xylene	OSHA PEL	PEL 100 ppm 435 mg/m3 ; TWA value 100 ppm 435 mg/m3 ; STEL value 150 ppm 655 mg/m3 ;
	ACGIH TLV	TWA value 100 ppm ; STEL value 150 ppm ;

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 9/17
(30786079/SDS_GEN_CA/EN)

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	aerosol
Odour:	characteristic
Odour threshold:	No applicable information available.
Colour:	colourless
pH value:	No applicable information available.
Melting point:	No applicable information available.
Freezing point:	No applicable information available.
Boiling point:	-24.90 °C

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 10/17
(30786079/SDS_GEN_CA/EN)

Sublimation point:	No applicable information available.
Flash point:	-42.00 °C
Flammability:	No applicable information available.
Lower explosion limit:	3.00 %(V)
Upper explosion limit:	18.60 %(V)
Autoignition:	No applicable information available.
Vapour pressure:	2.60 mmHg (20 °C)
Relative density:	0.7659 (20 °C)
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No applicable information available.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	miscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 11/17
(30786079/SDS_GEN_CA/EN)

Hazardous decomposition products

Decomposition products:
carbon dioxide, carbon monoxide

Thermal decomposition:
No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry
Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Virtually nontoxic by inhalation. Of moderate toxicity after single ingestion. Of high toxicity after short-term skin contact.

Information on: cyclohexanone
Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of moderate toxicity after short-term inhalation. Of moderate toxicity after short-term skin contact.

Information on: pentyl acetate
Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an acute hazard.

Information on: Xylene
Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 12/17
(30786079/SDS_GEN_CA/EN)

substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.

Oral

Type of value: LD50
Species: rat
Value: 1,890.000000 mg/kg

Inhalation

Type of value: LC50
Species: rat
Value: > 6.200000 mg/l

Dermal

Type of value: LD50
Species: rabbit
Value: > 794.000000 mg/kg

Assessment other acute effects

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Corrosive. Eye contact causes irritation.

Information on: cyclohexanone

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: n-Butyl acetate

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.
Not irritating to the skin. May cause slight irritation to the eyes.*

Information on: ethyl acetate

Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation. EU-classification Repeated or prolonged skin contact can cause drying and cracking of the skin.

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 13/17
(30786079/SDS_GEN_CA/EN)

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Sensitization

Information on: cyclohexanone

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies. Human data do not fully exclude a skin sensitizing potential.

Aspiration Hazard

No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: 1-methoxy-2-propylacetate

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Information on: n-Butyl acetate

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.

Information on: ethyl acetate

Assessment of repeated dose toxicity: The substance may cause damage to the olfactory epithelium after repeated inhalation. Based on available Data, the classification criteria are not met.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity.

Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 14/17
(30786079/SDS_GEN_CA/EN)

Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

Information on: cyclohexanone

Assessment of carcinogenicity: In long-term animal studies in which the substance was given in the drinking water in high doses, a carcinogenic effect was observed. Due to the rat-specific mode of action, no carcinogenic effects are expected in man. Hence, the findings are of low relevance for humans. IARC Group 3 (not classifiable as to human carcinogenicity).

Reproductive toxicity

Information on: ethyl acetate

Assessment of reproduction toxicity: Repeated inhalative uptake of the substance did not cause damage to the reproductive organs. In high doses a potential to impair fertility cannot be fully excluded. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Teratogenicity

Information on: cyclohexanone

Assessment of teratogenicity: The substance did not cause malformations in animal studies; however, toxicity to development was observed at high doses that were toxic to the parental animals.

Information on: ethyl acetate

Assessment of teratogenicity: The substance did not cause malformations in animal studies; however, toxicity to development was observed at high doses that were toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Xylene

Assessment of teratogenicity: In animal studies the substance did not cause malformations.

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 15/17
(30786079/SDS_GEN_CA/EN)

12. Ecological Information

No applicable information available.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Container disposal:

WARNING: Empty containers may still contain hazardous residue. Facility must be capable of handling empty aerosol cans. Do not cut, puncture, crush, or incinerate empty aerosol containers.

14. Transport Information

Land transport

TDG

Hazard class:	2.1
ID number:	UN 1950
Hazard label:	2.1
Proper shipping name:	AEROSOLS

Sea transport

IMDG

Hazard class:	2.1
ID number:	UN 1950
Hazard label:	2.1
Marine pollutant:	NO



We create chemistry

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08
Version: 7.0

Page: 16/17
(30786079/SDS_GEN_CA/EN)

Proper shipping name: AEROSOLS

Air transport

IATA/ICAO

Hazard class: 2.1
ID number: UN 1950
Hazard label: 2.1
Proper shipping name: AEROSOLS, FLAMMABLE

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 2 Fire: 4 Reactivity: 3 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2020/09/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.



We create chemistry

Safety Data Sheet

65U-10 Clearcoat Blender

Revision date : 2020/09/08

Version: 7.0

Page: 17/17

(30786079/SDS_GEN_CA/EN)

END OF DATA SHEET