



We create chemistry

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 1/14
(30781264/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

21-11 AdPro/Sealer

Recommended use of the chemical and restriction on use

Recommended use*: Coatings and related products

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Aquatic Acute	3	Hazardous to the aquatic environment - acute
Flam. Liq.	3	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 2/14
(30781264/SDS_GEN_CA/EN)

STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Central nervous system, Kidney, Auditory organ, Liver) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe dust or mist.
P240	Ground and bond container and receiving equipment.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332 + P313	If skin irritation occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 3/14
(30781264/SDS_GEN_CA/EN)

No applicable information available.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

1,2,4-trimethylbenzene

CAS Number: 95-63-6
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: 1,2,4-Trimethylbenzene

cumene

CAS Number: 98-82-8
Content (W/W): $\geq 0.2 - < 0.3\%$
Synonym: (1-Methylethyl)benzene; Isopropylbenzene, Cumene

ethylbenzene

CAS Number: 100-41-4
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: Ethylbenzene

chlorobenzene

CAS Number: 108-90-7
Content (W/W): $\geq 0.3 - < 1.0\%$
Synonym: Monochlorobenzene; MCB, Chlorobenzene

2-butoxyethyl acetate

CAS Number: 112-07-2
Content (W/W): $\geq 3.0 - < 5.0\%$
Synonym: Butyl cellosolve acetate

n-Butyl acetate

CAS Number: 123-86-4
Content (W/W): $\geq 10.0 - < 15.0\%$
Synonym: n-Butyl acetate

Xylene

CAS Number: 1330-20-7
Content (W/W): $\geq 10.0 - < 15.0\%$
Synonym: Xylene; Dimethylbenzene

Barium sulfate

CAS Number: 7727-43-7
Content (W/W): $\geq 10.0 - < 15.0\%$
Synonym: Barium sulfate, natural

talc

CAS Number: 14807-96-6
Content (W/W): $\geq 10.0 - < 15.0\%$
Synonym: hydrated magnesium silicate

solvent naphtha (petroleum), light aromatic, $< 0.1\%$ benzene

CAS Number: 64742-95-6
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: No data available.

Titanium oxide (TiO₂)

CAS Number: 13463-67-7

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 4/14
(30781264/SDS_GEN_CA/EN)

Content (W/W): ≥ 3.0 - $< 5.0\%$
Synonym: Titanium dioxide

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

If irritation develops, seek medical attention. Wash affected areas with water for at least 15 minutes.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: 1,2,4-trimethylbenzene

Symptoms: Overexposure may cause:, headache, tiredness, nausea, anxiety, asthma, bronchitis, noncardiogenic pulmonary edema

Information on: cumene

Symptoms: Overexposure may cause:, unconsciousness, coordination disorder, headache, dizziness

Information on: 2-butoxyethyl acetate

Symptoms: Overexposure may cause:, vomiting, polyuria, renal failure, nausea, headache

Information on: Xylene

Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Information on: talc

Symptoms: Overexposure may cause:, vomiting, convulsions, cyanosis, irregular breathing, dyspnea

Information on: solvent naphtha (petroleum), light aromatic, $<0.1\%$ benzene

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 5/14
(30781264/SDS_GEN_CA/EN)

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 6/14
(30781264/SDS_GEN_CA/EN)

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethyleneterephthalate (PET), Polypropylene (PP), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.
Protect from temperatures above: 49 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

1,2,4-trimethylbenzene	ACGIH, US:	TWA value 25 ppm ;
cumene	OSHA Z1:	Skin Designation ; The substance can be absorbed through the skin.
	OSHA Z1:	PEL 50 ppm 245 mg/m3 ;
	ACGIH, US:	TWA value 5 ppm ;
ethylbenzene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
chlorobenzene	ACGIH, US:	TWA value 10 ppm ;
	OSHA Z1:	PEL 75 ppm 350 mg/m3 ;
2-butoxyethyl acetate	ACGIH, US:	TWA value 20 ppm ;
n-Butyl acetate	ACGIH, US:	STEL value 150 ppm ;
	ACGIH, US:	TWA value 50 ppm ;
	OSHA Z1:	PEL 150 ppm 710 mg/m3 ;

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18

Version: 12.0

Page: 7/14

(30781264/SDS_GEN_CA/EN)

Xylene	ACGIH, US: ACGIH, US: OSHA Z1:	TWA value 100 ppm ; STEL value 150 ppm ; PEL 100 ppm 435 mg/m3 ;
carbon black	ACGIH, US: OSHA Z1:	TWA value 3 mg/m3 Inhalable fraction ; PEL 3.5 mg/m3 ;
Barium sulfate	ACGIH, US: OSHA Z1: OSHA Z1:	TWA value 5 mg/m3 Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica. PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ;
talc	ACGIH, US: OSHA Z3: OSHA Z3: OSHA Z3:	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica. TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10mg/m^3/(\%SiO_2+2)$, using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits.
Titanium oxide (TiO ₂)	ACGIH, US: OSHA Z1: OSHA Z3: OSHA Z3:	TWA value 10 mg/m3 ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 8/14
(30781264/SDS_GEN_CA/EN)

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	of acetate	
Odour threshold:	No applicable information available.	
Colour:	grey	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	No applicable information available.	
Sublimation point:	No applicable information available.	
Flash point:	> 27 °C	(ISO 3679)
Flammability:	No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.2289 g/cm ³ (20 °C)	
Relative density:	1.2290 (20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	195.500 mm ² /s	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 9/14
(30781264/SDS_GEN_CA/EN)

Hazardous decomposition products

Decomposition products:
carbon dioxide, carbon monoxide

Thermal decomposition:
No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Information on: 1,2,4-trimethylbenzene

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Information on: cumene

Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Information on: ethylbenzene

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.

Information on: chlorobenzene

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Of moderate toxicity after short-term inhalation. Of low toxicity after single ingestion.

Information on: 2-butoxyethyl acetate

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of moderate toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified this substance as 'harmful' after inhalation.

Information on: Xylene

Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.

Oral

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 10/14
(30781264/SDS_GEN_CA/EN)

Type of value: LD50
Species: rat
Value: 1,880.000000 mg/kg

Inhalation

Type of value: LC50
Species: rat
Value: 17.200000 mg/l

Dermal

Type of value: LD50
Species: rabbit
Value: 1,500.000000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Information on: 1,2,4-trimethylbenzene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: cumene

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes. Causes temporary irritation of the respiratory tract.

Information on: ethylbenzene

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: chlorobenzene

Assessment of irritating effects: Irritating to eyes and skin.

Information on: n-Butyl acetate

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.
Not irritating to the skin. May cause slight irritation to the eyes.*

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Information on: solvent naphtha (petroleum), light aromatic, <0.1% benzene

Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 11/14
(30781264/SDS_GEN_CA/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

Information on: chlorobenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Information on: 2-butoxyethyl acetate

Assessment of repeated dose toxicity: Damages blood cells. Due to the species specific mode of action, the effects are not expected to occur in humans.

Information on: n-Butyl acetate

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Information on: Barium sulfate

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.

Information on: solvent naphtha (petroleum), light aromatic, <0.1% benzene

Assessment of repeated dose toxicity: Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. After repeated exposure the prominent effect is local irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Information on: solvent naphtha (petroleum), light aromatic, <0.1% benzene

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not genotoxic in mammalian cell culture. The substance was not genotoxic in a test with mammals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Information on: cumene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 12/14
(30781264/SDS_GEN_CA/EN)

increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: Titanium oxide (TiO₂)

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. EU-classification IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Information on: chlorobenzene

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies. Literature data.

Information on: solvent naphtha (petroleum), light aromatic, <0.1% benzene

Assessment of teratogenicity: The potential to cause toxicity to development cannot be excluded at maternally toxic doses.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18
Version: 12.0

Page: 13/14
(30781264/SDS_GEN_CA/EN)

Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

14. Transport Information

Land transport

TDG

Hazard class: 3
Packing group: III
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1263
Hazard label: 3
Marine pollutant: NO
Proper shipping name: PAINT

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released; restriction on quantity / not listed

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2022/03/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our

Safety Data Sheet

21-11 AdPro/Sealer

Revision date : 2022/03/18

Version: 12.0

Page: 14/14

(30781264/SDS_GEN_CA/EN)

commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET