



We create chemistry

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 1/12  
(30782036/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

**49-W516 Silver Green**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Basecoat product

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

|                   |   |  |
|-------------------|---|--|
| Skin Corr./Irrit. | 2   | Skin corrosion/irritation                        |
| Eye Dam./Irrit.   | 1   | Serious eye damage/eye irritation                |
| Skin Sens.        | 1   | Skin sensitization                               |
| STOT SE           | 3 (Vapours may cause drowsiness and dizziness.) | Specific target organ toxicity — single exposure |

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13

Version: 3.0

Page: 2/12

(30782036/SDS\_GEN\_US/EN)

Flam. Liq.

3

Flammable liquids

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

|      |                                      |
|------|--------------------------------------|
| H226 | Flammable liquid and vapour.         |
| H315 | Causes skin irritation.              |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage.           |
| H336 | May cause drowsiness or dizziness.   |

Precautionary Statements (Prevention):

|      |  |
|------|--|
| P280 | Wear protective gloves, protective clothing and eye protection or face protection.             |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P264 | Wash contaminated body parts thoroughly after handling.  |
| P242 | Use only non-sparking tools.   |
| P241 | Use explosion-proof electrical, ventilating and lighting equipment.                            |
| P243 | Take action to prevent static discharges.  |
| P233 | Keep container tightly closed.   |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P240 | Ground and bond container and receiving equipment.   |
| P272 | Contaminated work clothing should not be allowed out of the workplace.                         |

Precautionary Statements (Response):

|                    |  |
|--------------------|--|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P302 + P352        | IF ON SKIN: Wash with plenty of soap and water.  |
| P370 + P378        | In case of fire: Use water spray for extinction.   |
| P362 + P364        | Take off contaminated clothing and wash it before reuse.   |
| P310               | Immediately call a POISON CENTER or physician.   |
| P333 + P313        | If skin irritation or rash occurs: Get medical attention.  |
| P303 + P361 + P353 | IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.                 |
| P304 + P340        | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

Precautionary Statements (Storage):

|             |  |
|-------------|--|
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool.                     |
| P405        | Store locked up.   |

Precautionary Statements (Disposal):

|      |   |
|------|---|
| P501 | Dispose of contents and container to hazardous or special waste collection point. |
|------|---|

**Hazards not otherwise classified**

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 3/12  
(30782036/SDS\_GEN\_US/EN)

No applicable information available.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

##### 1-methoxypropan-2-ol

CAS Number: 107-98-2

Content (W/W):  $\geq 20.0$  -  $< 25.0\%$

Synonym: 1-Methoxy-2-propanol; Propylene glycol monomethyl ether

##### 2-dimethylaminoethanol

CAS Number: 108-01-0

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: N,N-Dimethyl(2-hydroxyethyl)amine; 2(Dimethylamino)ethanol, Deanol

##### 1-methoxy-2-propylacetate

CAS Number: 108-65-6

Content (W/W):  $\geq 15.0$  -  $< 20.0\%$

Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

##### 2-butoxyethanol

CAS Number: 111-76-2

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: Butyl cellosolve

##### 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

CAS Number: 126-86-3

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: 2,4,7,9-Tetramethyl-5-decyne-4,7-diol

##### 2-Propanol, 1-propoxy-

CAS Number: 1569-01-3

Content (W/W):  $\geq 1.0$  -  $< 3.0\%$

Synonym: 1-Propoxy-2-propanol; 1,2-Propylene glycol 1-propyl ether

##### Magnesium fluoride (MgF<sub>2</sub>)

CAS Number: 7783-40-6

Content (W/W):  $\geq 7.0$  -  $< 10.0\%$

Synonym: Magnesium fluoride

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 4/12  
(30782036/SDS\_GEN\_US/EN)

### If on skin:

Seek medical attention. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed.

### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

## Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: 1-methoxypropan-2-ol*

*Symptoms: Overexposure may cause:, lacrimation*

*Information on: 2-dimethylaminoethanol*

*Symptoms: Overexposure may cause:, dyspnea, restlessness, coughing, headache*

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Symptoms: Overexposure may cause:, corneal injury, severe pain, skin irritation, erythema, nausea, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: 2-Propanol, 1-propoxy-*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: Magnesium fluoride (MgF<sub>2</sub>)*

*Symptoms: No data available.*

## Indication of any immediate medical attention and special treatment needed

### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13

Version: 3.0

Page: 5/12

(30782036/SDS\_GEN\_US/EN)

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethyleneterephthalate (PET), Polypropylene (PP), tinned carbon steel (Tinplate)

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 6/12  
(30782036/SDS\_GEN\_US/EN)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:  
Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

|                           |                                    |  |
|---------------------------|------------------------------------|--|
| 1-methoxypropan-2-ol      | ACGIH, US:<br>ACGIH, US:           | TWA value 50 ppm ;<br>STEL value 100 ppm ;   |
| 2-butoxyethanol           | ACGIH, US:<br>OSHA Z1:<br>OSHA Z1: | TWA value 20 ppm ;<br>PEL 50 ppm 240 mg/m3 ;<br>Skin Designation ; The substance can be absorbed through the skin. |
| chromium                  | OSHA Z1:<br>ACGIH, US:             | PEL 1 mg/m3 (Chromium (Cr));<br>TWA value 0.5 mg/m3 Inhalable fraction (Cr (0));                                   |
| Magnesium fluoride (MgF2) | ACGIH, US:<br>OSHA Z1:<br>OSHA Z2: | TWA value 2.5 mg/m3 (fluorine (F));<br>PEL 2.5 mg/m3 (fluorine (F));<br>TWA value 2.5 mg/m3 dust ;                 |

### **Advice on system design:**

Provide local exhaust ventilation to maintain recommended P.E.L.  
General mechanical ventilation should comply with OSHA 1910.94.

### Personal protective equipment

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### **Hand protection:**

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13

Version: 3.0

Page: 7/12

(30782036/SDS\_GEN\_US/EN)

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

|   |                                      |              |
|---|--------------------------------------|--------------|
| Form:   | liquid                               |              |
| Odour:  | aromatic                             |              |
| Odour threshold:                                    | No applicable information available. |              |
| Colour:   | green                                |              |
| pH value:   | No applicable information available. |              |
| Melting point:                                      | No applicable information available. |              |
| Freezing point:                                     | No applicable information available. |              |
| :   | 119.00 °C                            |              |
|   | 246.20 °F                            |              |
| Sublimation point:                                  | No applicable information available. |              |
| Flash point:  | 32 °C                                | (ISO 3679)   |
|   | 89.60 °F                             |              |
| Flammability:                                       | No applicable information available. |              |
| Lower explosion limit:                              | No applicable information available. |              |
| Upper explosion limit:                              | No applicable information available. |              |
| Autoignition:                                       | No applicable information available. |              |
| Vapour pressure:                                    | No applicable information available. |              |
| Density:  | 1.0879 g/cm3                         | (calculated) |
|   | ( 20 °C)                             |              |
|   | 9.0794 lb/USg                        | (calculated) |
| Relative density:                                   | 1.0880                               |              |
|   | ( 20 °C)                             |              |
| Vapour density:                                     | No applicable information available. |              |
| Partitioning coefficient n-octanol/water (log Pow): | No applicable information available. |              |
| Thermal decomposition:                              | No applicable information available. |              |
| Viscosity, dynamic:                                 | No applicable information available. |              |
| Viscosity, kinematic:                               | 411.600 mm2/s                        |              |
| Solubility in water:                                | No applicable information available. |              |
| Miscibility with water:                             | immiscible                           |              |
| Solubility (quantitative):                          | No applicable information available. |              |
| Solubility (qualitative):                           | No applicable information available. |              |
| Molar mass:   | No applicable information available. |              |
| Evaporation rate:                                   | No applicable information available. |              |

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 8/12  
(30782036/SDS\_GEN\_US/EN)

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

Thermal decomposition:  
No applicable information available.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

#### *Information on: 1-methoxypropan-2-ol*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.*

#### *Information on: 2-dimethylaminoethanol*

*Assessment of acute toxicity: Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation.*

#### *Information on: 2-butoxyethanol*

*Assessment of acute toxicity: Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified this substance as 'harmful' after inhalation. Virtually nontoxic after a single skin contact.*

#### *Information on: 2-Propanol, 1-propoxy-*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Of low toxicity after short-term skin contact.*

-----

#### Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

*Information on: 2-dimethylaminoethanol*



# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 9/12  
(30782036/SDS\_GEN\_US/EN)

*Assessment of irritating effects: Corrosive! Damages skin and eyes.*

*Information on: 2-butoxyethanol*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Assessment of irritating effects: Not irritating to the skin. May cause severe damage to the eyes.*

*Information on: 2-Propanol, 1-propoxy-*

*Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation.*

### Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Assessment of sensitization:*

*Caused skin sensitization in animal studies.*

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

*Information on: 1-methoxypropan-2-ol*

*Assessment of repeated dose toxicity: May affect the liver as indicated in animal studies. The substance may cause damage to the kidney after repeated inhalation. Effect found in rodents only. The relevance to humans is questionable.*

*Information on: 2-dimethylaminoethanol*

*Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated ingestion of high doses. The results are preliminary and do not provide a complete understanding of the effect observed. After repeated administration the prominent effect is the induction of corrosion.*

*The substance may cause damage to the central nervous system after repeated ingestion of high doses. The results are preliminary and do not provide a complete understanding of the effect observed.*

*Information on: 1-methoxy-2-propylacetate*

*Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.*

*Information on: 2-butoxyethanol*

*Assessment of repeated dose toxicity: Damages blood cells. Due to the species specific mode of action, the effects are not expected to occur in humans.*

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 10/12  
(30782036/SDS\_GEN\_US/EN)

### Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

#### *Information on: 2-dimethylaminoethanol*

*Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was not observed. Under certain conditions the substance can form nitrosamines. Nitrosamines are carcinogenic in animal studies.*

#### *Information on: 2-butoxyethanol*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

#### *Information on: 1-methoxypropan-2-ol*

*Assessment of reproduction toxicity: The potential to impair fertility cannot be excluded when given at maternally toxic doses.*

#### *Information on: 2-dimethylaminoethanol*

*Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The results were determined in a Screening test. On the basis of currently available information, a final assessment is not possible.*

-----

### Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

#### *Information on: 2-dimethylaminoethanol*

*Assessment of teratogenicity: Causes developmental effects in animals at high, maternally toxic doses.*

#### *Information on: Magnesium fluoride (MgF<sub>2</sub>)*

*Assessment of teratogenicity: The substance did not cause malformations in animal studies; however, toxicity to development was observed at high doses that were toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

---

## 12. Ecological Information

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways.

Based on available data, the classification criteria are not met.

---

## 13. Disposal considerations

**Waste disposal of substance:**

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13

Version: 3.0

Page: 11/12

(30782036/SDS\_GEN\_US/EN)

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

## 14. Transport Information

### Land transport

USDOT

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Proper shipping name: | PAINT   |

### Sea transport

IMDG

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Marine pollutant:     | NO      |
| Proper shipping name: | PAINT   |

### Air transport

IATA/ICAO

|                       |         |
|-----------------------|---------|
| Hazard class:         | 3       |
| Packing group:        | III     |
| ID number:            | UN 1263 |
| Hazard label:         | 3       |
| Proper shipping name: | PAINT   |

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

#### EPCRA 313:

##### CAS Number

111-76-2

##### Chemical name

2-butoxyethanol

# Safety Data Sheet

## 49-W516 Silver Green

Revision date : 2022/03/13  
Version: 3.0

Page: 12/12  
(30782036/SDS\_GEN\_US/EN)

### State regulations

#### State RTK

| State RTK | CAS Number | Chemical name  |
|-----------|------------|--|
|           |            |  |
| NJ        | 107-98-2   | 1-methoxypropan-2-ol                                     |
|           | 108-01-0   | 2-dimethylaminoethanol                                   |
|           | 111-76-2   | 2-butoxyethanol  |
|           | 7783-40-6  | Magnesium fluoride (MgF <sub>2</sub> )                   |
| PA        | 107-98-2   | 1-methoxypropan-2-ol                                     |
|           | 108-01-0   | 2-dimethylaminoethanol                                   |
|           | 111-76-2   | 2-butoxyethanol  |
|           | 7440-47-3  | chromium   |
|           | 7783-40-6  | Magnesium fluoride (MgF <sub>2</sub> )                   |
|           | 68611-44-9 | Silane, dichlorodimethyl-, reaction products with silica |

#### **NFPA Hazard codes:**

Health: 3      Fire: 3      Reactivity: 0      Special:

#### **HMIS III rating**

Health: 3      Flammability: 3      Physical hazard: 0

## 16. Other Information

#### **SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2022/03/13

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET