

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date : 2023/05/18
Version: 9.0

Page: 1/15
(30779297/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

35-M218 Silvr Dollar Fine

Recommended use of the chemical and restriction on use

Recommended use*: Basecoat product

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.

2

Eye Dam./Irrit.

1

STOT SE

3 (irritating to
respiratory system,
Vapours may cause

Skin corrosion/irritation

Serious eye damage/eye irritation

Specific target organ toxicity — single exposure

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 2/15
(30779297/SDS_GEN_US/EN)

	drowsiness and dizziness.)	
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Flam. Liq.	2	Flammable liquids
Carc.	2	Carcinogenicity
STOT RE	1	Specific target organ toxicity — repeated exposure
STOT RE	2	Specific target organ toxicity — repeated exposure

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Central nervous system, Auditory organ, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P273	Avoid release to the environment.
P260	Do not breathe mist or vapour or spray.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P270	Do not eat, drink or smoke when using this product.
P201	Obtain special instructions before use.

Precautionary Statements (Response):

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 3/15
(30779297/SDS_GEN_US/EN)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or physician.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313 If skin irritation occurs: Get medical attention.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P370 + P378 In case of fire: Use water spray for extinction.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P308 + P313 IF exposed or concerned: Get medical attention.
P314 Get medical advice/attention if you feel unwell.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazards not otherwise classified

Labeling of special preparations (GHS):

May cause cancer. Contains formaldehyde. This product is capable of releasing formaldehyde into the air.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

n-butanol

CAS Number: 71-36-3
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: 1-Butanol; n-Butanol

Isobutanol

CAS Number: 78-83-1
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: 2-Methyl-1-propanol; Isobutanol

ethylbenzene

CAS Number: 100-41-4
Content (W/W): $\geq 1.0 - < 3.0\%$
Synonym: Ethylbenzene

4-methylpentan-2-one

CAS Number: 108-10-1
Content (W/W): $\geq 15.0 - < 20.0\%$
Synonym: isobutyl methyl ketone

cyclohexane

CAS Number: 110-82-7

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 4/15
(30779297/SDS_GEN_US/EN)

Content (W/W): ≥ 0.1 - $< 0.2\%$
Synonym: Hexahydrobenzene; Cyclohexane

n-Butyl acetate
CAS Number: 123-86-4
Content (W/W): ≥ 25.0 - $< 50.0\%$
Synonym: Essigsäure-n-butylester

Xylene
CAS Number: 1330-20-7
Content (W/W): ≥ 7.0 - $< 10.0\%$
Synonym: Xylene; Dimethylbenzene

Naphtha (petroleum), hydrodesulfurized heavy, Flpoint $< 55^{\circ}\text{C}$
CAS Number: 64742-82-1
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: No data available.

Aluminum
CAS Number: 7429-90-5
Content (W/W): ≥ 3.0 - $< 5.0\%$
Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Seek medical attention. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 5/15
(30779297/SDS_GEN_US/EN)

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: n-butanol

Symptoms: Overexposure may cause:, headache, dizziness, coordination disorder, coma, lacrimation, loss of hearing

Information on: Isobutanol

Symptoms: Overexposure may cause:, coma, coordination disorder, headache, dizziness

Information on: ethylbenzene

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, irritation of the mucous membranes, erythema, nausea, headache, dizziness, diarrhea, abdominal cramps, dermatitis, loss of hearing, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse

Information on: 4-methylpentan-2-one

Symptoms: Overexposure may cause:, vomiting, weakness, coordination disorder, nausea, headache, dizziness

Information on: cyclohexane

Symptoms: Overexposure may cause:, unconsciousness, lethargy, dizziness

Information on: n-Butyl acetate

Symptoms: Overexposure may cause:, unconsciousness, vomiting, weakness, coordination disorder, nausea, diarrhea, coughing, headache

Information on: Xylene

Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: Aluminum

Symptoms: No data available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.
------------	---

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 6/15
(30779297/SDS_GEN_US/EN)

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 7/15
(30779297/SDS_GEN_US/EN)

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Formaldehyde	ACGIH, US:	STEL value 0.3 ppm ;
	ACGIH, US:	TWA value 0.1 ppm ;
	OSHA, US:	STEL value 2 ppm ;
	OSHA, US:	OSHA Action level 0.5 ppm ;
	OSHA, US:	TWA value 0.75 ppm ;
n-butanol	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 300 mg/m3 ;
Isobutanol	ACGIH, US:	TWA value 50 ppm ;
	OSHA Z1:	PEL 100 ppm 300 mg/m3 ;
ethylbenzene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
4-methylpentan-2-one	ACGIH, US:	STEL value 75 ppm ;
	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 410 mg/m3 ;
cyclohexane	ACGIH, US:	TWA value 100 ppm ;
	OSHA Z1:	PEL 300 ppm 1,050 mg/m3 ;
n-Butyl acetate	ACGIH, US:	STEL value 150 ppm ;
	ACGIH, US:	TWA value 50 ppm ;
	OSHA Z1:	PEL 150 ppm 710 mg/m3 ;
Xylene	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
	ACGIH, US:	TWA value 20 ppm ;

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 8/15
(30779297/SDS_GEN_US/EN)

Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C Aluminum	ACGIH, US:	TWA value 100 ppm ;
	OSHA Z1:	PEL 500 ppm 2,900 mg/m3 ;
	ACGIH, US:	TWA value 1 mg/m3 Respirable fraction ;
	OSHA Z1:	PEL 5 mg/m3 Respirable fraction (aluminum (Al));
	OSHA Z1:	PEL 15 mg/m3 Total dust (aluminum (Al));

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

General mechanical ventilation should comply with OSHA 1910.94. Minimal concentrations of free formaldehyde may be liberated during the cross-linking/curing in curing ovens (i.e. baking).

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid
Odour:	of hydrocarbons
Odour threshold:	No applicable information available.
Colour:	silver colours
pH value:	No applicable information available.
Melting point:	No applicable information available.
Freezing point:	No applicable information available.
Boiling range:	0 - 145 °C 0 - 293 °F

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 9/15
(30779297/SDS_GEN_US/EN)

Sublimation point:	No applicable information available.	
Flash point:	20 °C 68 °F	(ISO 3679) (ISO 3679)
Flammability:	The product burns self-sustainingly No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	21.50 hPa (20 °C)	
Density:	No applicable information available. 0.924 g/cm3 (20 °C) 7.7112 lb/USg	
Relative density:	0.9240 (20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Thermal decomposition:	No applicable information available.	
Viscosity, kinematic:	411.6 mm2/s (23 °C) 755.000 mm2/s (40 °C)	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:
nitrogen oxides, carbon dioxide, carbon monoxide
formaldehyde

Thermal decomposition:

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 10/15
(30779297/SDS_GEN_US/EN)

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

Type of value: ATE

Value: 16,420 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: ATE

Value: 66 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: n-butanol

Assessment of irritating effects: Skin contact causes irritation. Risk of serious damage to eyes.

Information on: Isobutanol

Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes irritation.

Information on: ethylbenzene

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 11/15
(30779297/SDS_GEN_US/EN)

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: cyclohexane

Assessment of irritating effects: Skin contact causes irritation. EU-classification Not irritating to the eyes.

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

Information on: 4-methylpentan-2-one

Assessment of repeated dose toxicity: May affect the liver and kidneys as indicated in animal studies.

Information on: cyclohexane

Assessment of repeated dose toxicity: Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure.

Information on: n-Butyl acetate

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C

Assessment of repeated dose toxicity: Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

EU-classification Repeated exposure to small quantities may affect certain organs. Damages the central nerve system.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 12/15
(30779297/SDS_GEN_US/EN)

Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C
Assessment of mutagenicity: Capable of causing genetic defects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: 4-methylpentan-2-one

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. EU-classification IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C

Assessment of carcinogenicity: The substance caused cancer in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Information on: n-butanol

Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The potential to cause toxicity to development cannot be excluded when given in high doses.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 13/15
(30779297/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

Sea transport

IMDG

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

Air transport

IATA/ICAO

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18
Version: 9.0

Page: 14/15
(30779297/SDS_GEN_US/EN)

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number

100-41-4	Chemical name
108-10-1	ethylbenzene
71-36-3	4-methylpentan-2-one
1330-20-7	n-butanol
7429-90-5	Xylene
	Aluminum

State regulations

State RTK

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	71-36-3	n-butanol
	78-83-1	Isobutanol
	100-41-4	ethylbenzene
	108-10-1	4-methylpentan-2-one
	123-86-4	n-Butyl acetate
	1330-20-7	Xylene
PA	64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C
	50-00-0	Formaldehyde
	71-36-3	n-butanol
	78-83-1	Isobutanol
	100-41-4	ethylbenzene
	108-10-1	4-methylpentan-2-one
	123-86-4	n-Butyl acetate
	1330-20-7	Xylene
	64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C
	7429-90-5	Aluminum

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including METHYL ISOBUTYL KETONE (MIBK), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 3 Reactivity: 0 Special:

HMIS III rating

Health: 2^a Flammability: 3 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2023/05/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring

Safety Data Sheet

35-M218 Silvr Dollar Fine

Revision date: 2023/05/18

Version: 9.0

Page: 15/15

(30779297/SDS_GEN_US/EN)

the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET