

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date : 2023/11/02  
Version: 6.0

Page: 1/14  
(30778184/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

#### 60U-20 Reducer Normal

#### Recommended use of the chemical and restriction on use

Recommended use\*: Thinner

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Synonyms: PAINT RELATED MATERIAL

### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

STOT SE

3 (May cause  
drowsiness and  
dizziness.)

Specific target organ toxicity — single exposure

Flam. Liq.

3

Flammable liquids

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 2/14  
(30778184/SDS\_GEN\_US/EN)

Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Skin Corr./Irrit.	2	Skin corrosion/irritation
Repr.	2 (fertility, unborn child)	Reproductive toxicity
STOT RE	1	Specific target organ toxicity — repeated exposure
Asp. Tox.	1	Aspiration hazard
STOT RE	2	Specific target organ toxicity — repeated exposure

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Central nervous system, Peripheral nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P202	Do not handle until all safety precautions have been read and understood.
P240	Ground and bond container and receiving equipment.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P264	Wash contaminated body parts thoroughly after handling.
P260	Do not breathe mist or vapour or spray.

Precautionary Statements (Response):

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 3/14  
(30778184/SDS\_GEN\_US/EN)

P312	Call a POISON CENTER or physician if you feel unwell.
P331	Do NOT induce vomiting.
P314	Get medical advice/attention if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332 + P313	If skin irritation occurs: Get medical attention.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use water spray for extinction.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

### Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

### Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### n-Butyl acetate

CAS Number: 123-86-4  
Content (W/W):  $\geq 50.0$  -  $< 75.0\%$   
Synonym: Essigsäure-n-butylester

#### 1-methoxy-2-propylacetate

CAS Number: 108-65-6  
Content (W/W):  $\geq 10.0$  -  $< 15.0\%$   
Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

#### Naphtha (petroleum), hydrodesulfurized heavy, Flpoint $< 55^{\circ}\text{C}$

CAS Number: 64742-82-1  
Content (W/W):  $\geq 10.0$  -  $< 15.0\%$   
Synonym: No data available.

#### Solvent naphtha (petroleum), light arom.

CAS Number: 64742-95-6  
Content (W/W):  $\geq 7.0$  -  $< 10.0\%$   
Synonym: No data available.

#### 2-butoxyethyl acetate

CAS Number: 112-07-2  
Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: (2-Butoxyethyl)acetat

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 4/14  
(30778184/SDS\_GEN\_US/EN)

solvent naphtha, light aliph., Low boiling P., <0,1% benzene  
CAS Number: 64742-89-8  
Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: No data available.

ethylbenzene  
CAS Number: 100-41-4  
Content (W/W):  $\geq 0.1$  -  $< 0.2\%$   
Synonym: Ethylbenzene

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: ethylbenzene*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, irritation of the mucous membranes, erythema, nausea, headache, dizziness, diarrhea, abdominal cramps, dermatitis, loss of hearing, Ingestion may provoke the following symptoms:; asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse*

*Information on: 1-methoxy-2-propylacetate*

*Symptoms: Overexposure may cause:; nausea, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: 2-butoxyethyl acetate*

*Symptoms: Overexposure may cause:; vomiting, polyuria, renal failure, nausea, headache*

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 5/14  
(30778184/SDS\_GEN\_US/EN)

*Information on: n-Butyl acetate*

*Symptoms: Overexposure may cause:; unconsciousness, vomiting, weakness, coordination disorder, nausea, diarrhea, coughing, headache*

*Information on: Solvent naphtha (petroleum), light arom.*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:; asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death*

*Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: solvent naphtha, light aliph., Low boiling P., <0,1% benzene*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 6/14  
(30778184/SDS\_GEN\_US/EN)

---

### 6. Accidental release measures

#### **Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

#### **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

#### **Methods and material for containment and cleaning up**

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

### 7. Handling and Storage

#### **Precautions for safe handling**

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

#### **Conditions for safe storage, including any incompatibilities**

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

---

### 8. Exposure Controls/Personal Protection

#### **Components with occupational exposure limits**

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 7/14  
(30778184/SDS\_GEN\_US/EN)

ethylbenzene	ACGIH, US: OSHA Z1:	TWA value 20 ppm ; PEL 100 ppm 435 mg/m3 ;
2-butoxyethyl acetate	ACGIH, US:	TWA value 20 ppm ;
n-Butyl acetate	ACGIH, US: ACGIH, US: OSHA Z1:	STEL value 150 ppm ; TWA value 50 ppm ; PEL 150 ppm 710 mg/m3 ;
Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C	ACGIH, US: OSHA Z1:	TWA value 100 ppm ; PEL 500 ppm 2,900 mg/m3 ;
solvent naphtha, light aliph., Low boiling P., <0,1% benzene	OSHA Z1:	PEL 100 ppm 400 mg/m3 ;

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

General mechanical ventilation should comply with OSHA 1910.94.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

---

## 9. Physical and Chemical Properties

Form: liquid

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 8/14  
(30778184/SDS\_GEN\_US/EN)

Odour:	ester-like	
Odour threshold:	No applicable information available.	
Colour:	colourless	
pH value:	No applicable information available. substance/mixture is non- polar/aprotic	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	122 - 132 °C 252 - 270 °F	
Sublimation point:	No applicable information available.	
Flash point:	77 °F 25 °C	(ASTM D3278) (ASTM D3278)
Flammability:	The product burns self-sustainingly No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	13.00 hPa ( 20 °C) 61.00 hPa ( 50 °C)	
Density:	0.874 g/cm3 ( 20 °C) 7.2939 lb/USg	
Relative density:	0.874	
Vapour density:	Heavier than air.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	6.0 mm2/s ( 23 °C) ( 40 °C) No data available.	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid



# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 9/14  
(30778184/SDS\_GEN\_US/EN)

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

Thermal decomposition:  
No applicable information available.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

#### Oral

Type of value: ATE

Value: 62,617 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Inhalation

Type of value: ATE

Value: > 20 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Dermal

Type of value: ATE

Value: 49,950 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 10/14  
(30778184/SDS\_GEN\_US/EN)

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: solvent naphtha, light aliph., Low boiling P., <0,1% benzene*

*Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes.*

### Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

### Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

*Information on: 1-methoxy-2-propylacetate*

*Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.*

*Information on: n-Butyl acetate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion.*

*Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C*

*Assessment of repeated dose toxicity: Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.*

*EU-classification Repeated exposure to small quantities may affect certain organs. Damages the central nerve system.*

*Information on: solvent naphtha, light aliph., Low boiling P., <0,1% benzene*

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 11/14  
(30778184/SDS\_GEN\_US/EN)

*Assessment of repeated dose toxicity: Repeated exposure to large quantities may affect certain organs. Damages the kidneys. Due to the species specific mode of action, the effects are not expected to occur in humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

*Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C*

*Assessment of mutagenicity: Capable of causing genetic defects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C*

*Assessment of carcinogenicity: The substance caused cancer in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

*Information on: Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C*

*Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

---

## 12. Ecological Information

### Toxicity

#### Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 12/14  
(30778184/SDS\_GEN\_US/EN)

### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. No data available for the preparation.

## 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

Dispose of in accordance with national, state and local regulations.

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

## 14. Transport Information

### Land transport

USDOT

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT RELATED MATERIAL

### Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT RELATED MATERIAL

### Air transport

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT RELATED MATERIAL

## 15. Regulatory Information

### Federal Regulations

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02  
Version: 6.0

Page: 13/14  
(30778184/SDS\_GEN\_US/EN)

### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

### EPCRA 313:

<u>CAS Number</u>	Chemical name
100-41-4	ethylbenzene
112-07-2	2-butoxyethyl acetate

### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	112-07-2	2-butoxyethyl acetate
	123-86-4	n-Butyl acetate
	64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C
	64742-89-8	solvent naphtha, light aliph., Low boiling P., <0,1% benzene
	100-41-4	ethylbenzene
PA	112-07-2	2-butoxyethyl acetate
	123-86-4	n-Butyl acetate
	64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy, Flpoint < 55°C
	64742-89-8	solvent naphtha, light aliph., Low boiling P., <0,1% benzene

### Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

**WARNING:** This product can expose you to chemicals including ETHYLBENZENE, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

### HMIS III rating

Health: 2<sup>a</sup> Flammability: 3 Physical hazard: 0

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2023/11/02

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

# Safety Data Sheet

## 60U-20 Reducer Normal

Revision date: 2023/11/02

Version: 6.0

Page: 14/14

(30778184/SDS\_GEN\_US/EN)

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET