



We create chemistry

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date : 2023/05/18  
Version: 8.0

Page: 1/14  
(30779253/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

**35-M1910 Black Yellow**

**Recommended use of the chemical and restriction on use**

Recommended use\*: Basecoat product

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

---

### 2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

**Classification of the product**

Skin Corr./Irrit.

2

Skin corrosion/irritation

Eye Dam./Irrit.

2A

Serious eye damage/eye irritation

Aquatic Acute

3

Hazardous to the aquatic environment - acute

STOT SE

3 (irritating to  
respiratory system,

Specific target organ toxicity — single exposure

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 2/14  
(30779253/SDS\_GEN\_US/EN)

	Vapours may cause drowsiness and dizziness.)	
Flam. Liq.	2	Flammable liquids
STOT RE	2	Specific target organ toxicity — repeated exposure
Carc.	2	Carcinogenicity

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H402	Harmful to aquatic life.
H373	May cause damage to organs (Liver, Auditory organ, Central nervous system, Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe mist or vapour or spray.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.

Precautionary Statements (Response):

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 3/14  
(30779253/SDS\_GEN\_US/EN)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER or physician if you feel unwell.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P370 + P378 In case of fire: Use water spray for extinction.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P314 Get medical advice/attention if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.

### Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### ethylbenzene

CAS Number: 100-41-4  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: Ethylbenzene

#### 4-methylpentan-2-one

CAS Number: 108-10-1  
Content (W/W):  $\geq 10.0$  -  $< 15.0\%$   
Synonym: isobutyl methyl ketone

#### 1-methoxy-2-propylacetate

CAS Number: 108-65-6  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

#### 2-butoxyethanol

CAS Number: 111-76-2  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: 2-Butoxyethanol; Ethylene glycol monobutyl ether

#### n-Butyl acetate

CAS Number: 123-86-4  
Content (W/W):  $\geq 25.0$  -  $< 50.0\%$

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 4/14  
(30779253/SDS\_GEN\_US/EN)

Synonym: Essigsäure-n-butylester

Xylene

CAS Number: 1330-20-7  
Content (W/W):  $\geq 10.0$  -  $< 15.0\%$   
Synonym: Xylene; Dimethylbenzene

carbon black

CAS Number: 1333-86-4  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: C.I. 77266

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

##### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

##### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: ethylbenzene*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, irritation of the mucous membranes, erythema, nausea, headache, dizziness, diarrhea, abdominal cramps, dermatitis, loss of hearing, Ingestion may provoke the following symptoms:; asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse*

*Information on: 4-methylpentan-2-one*

*Symptoms: Overexposure may cause:; vomiting, weakness, coordination disorder, nausea, headache, dizziness*

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 5/14  
(30779253/SDS\_GEN\_US/EN)

*Information on: 1-methoxy-2-propylacetate*

*Symptoms: Overexposure may cause: nausea, vomiting, dizziness, diarrhea, abdominal cramps*

*Information on: 2-butoxyethanol*

*Symptoms: Overexposure may cause: skin irritation, irritation of respiratory tract, erythema, nausea, headache, vomiting, diarrhea, abdominal cramps, hemolysis, blood in urine, CNS depression*

*Information on: n-Butyl acetate*

*Symptoms: Overexposure may cause: unconsciousness, vomiting, weakness, coordination disorder, nausea, diarrhea, coughing, headache*

*Information on: Xylene*

*Symptoms: Overexposure may cause: coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness*

*Information on: carbon black*

*Symptoms: Overexposure may cause: rhinitis, irritation of the mucous membranes, irritates the eyes and respiratory tract, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps*

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 6/14  
(30779253/SDS\_GEN\_US/EN)

---

### 6. Accidental release measures

#### **Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

#### **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

#### **Methods and material for containment and cleaning up**

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

### 7. Handling and Storage

#### **Precautions for safe handling**

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not apply to hot surfaces.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

#### **Conditions for safe storage, including any incompatibilities**

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

---

### 8. Exposure Controls/Personal Protection

#### **Components with occupational exposure limits**

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 7/14  
(30779253/SDS\_GEN\_US/EN)

n-butanol	ACGIH, US: OSHA Z1:	TWA value 20 ppm ; PEL 100 ppm 300 mg/m3 ;
ethylbenzene	ACGIH, US: OSHA Z1:	TWA value 20 ppm ; PEL 100 ppm 435 mg/m3 ;
4-methylpentan-2-one	ACGIH, US: ACGIH, US: OSHA Z1:	STEL value 75 ppm ; TWA value 20 ppm ; PEL 100 ppm 410 mg/m3 ;
2-butoxyethanol	ACGIH, US: OSHA Z1: OSHA Z1:	TWA value 20 ppm ; PEL 50 ppm 240 mg/m3 ; Skin Designation ; The substance can be absorbed through the skin.
n-Butyl acetate	ACGIH, US: ACGIH, US: OSHA Z1:	STEL value 150 ppm ; TWA value 50 ppm ; PEL 150 ppm 710 mg/m3 ;
Xylene	OSHA Z1: ACGIH, US:	PEL 100 ppm 435 mg/m3 ; TWA value 20 ppm ;
carbon black	ACGIH, US: OSHA Z1:	TWA value 3 mg/m3 Inhalable fraction ; PEL 3.5 mg/m3 ;

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

General mechanical ventilation should comply with OSHA 1910.94.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 8/14  
(30779253/SDS\_GEN\_US/EN)

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	No data available.	
Odour threshold:	No applicable information available.	
Colour:	black	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	114.00 - 145.00 °C 237 - 293 °F	
Sublimation point:	No applicable information available.	
Flash point:	21 °C 70 °F	(ISO 3679) (ISO 3679)
Flammability:	The product burns self-sustainingly No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	8.00 hPa ( 20 °C) No applicable information available.	
Density:	0.929 g/cm <sup>3</sup> ( 20 °C) 7.7529 lb/USg	
Relative density:	0.9290 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	411.6 mm <sup>2</sup> /s ( 23 °C)	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability



# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 9/14  
(30779253/SDS\_GEN\_US/EN)

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

#### Oral

Type of value: ATE

Value: 18,818 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Inhalation

Type of value: ATE

Value: 78 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Dermal

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Assessment other acute effects

Assessment of STOT single:

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 10/14  
(30779253/SDS\_GEN\_US/EN)

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

#### *Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

#### *Information on: 2-butoxyethanol*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

#### *Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

### Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

#### *Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

#### *Information on: 4-methylpentan-2-one*

*Assessment of repeated dose toxicity: May affect the liver and kidneys as indicated in animal studies.*

#### *Information on: 1-methoxy-2-propylacetate*

*Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.*

#### *Information on: n-Butyl acetate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

#### *Information on: Xylene*

*Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney*

#### *Information on: carbon black*

*Assessment of repeated dose toxicity: Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease). The substance may cause*

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 11/14  
(30779253/SDS\_GEN\_US/EN)

*increase in lung mass and lung tissue changes after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects. Repeated dermal uptake of the substance did not cause substance-related effects.*

-----

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

#### *Information on: carbon black*

*Assessment of mutagenicity: Results from a number of mutagenicity studies with microorganisms and mammalian cell culture are available. Taking into account all of the information, there is no indication that the substance is mutagenic. Based on the structure, there is a suspicion of a mutagenic effect.*

*The substance was genotoxic in a test with mammals. The effect may result from a secondary mechanism.*

-----

### Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

#### *Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

#### *Information on: 4-methylpentan-2-one*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. EU-classification IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

#### *Information on: 2-butoxyethanol*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).*

#### *Information on: carbon black*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 12/14  
(30779253/SDS\_GEN\_US/EN)

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

---

## 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA-licensed facility. Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

---

## 14. Transport Information

### Land transport

USDOT

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

### Sea transport

IMDG

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

### Air transport

IATA/ICAO

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18  
Version: 8.0

Page: 13/14  
(30779253/SDS\_GEN\_US/EN)

### 15. Regulatory Information

#### Federal Regulations

##### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

##### **EPCRA 313:**

<u>CAS Number</u>	<u>Chemical name</u>
100-41-4	ethylbenzene
108-10-1	4-methylpentan-2-one
1330-20-7	Xylene
111-76-2	2-butoxyethanol

#### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	100-41-4	ethylbenzene
	108-10-1	4-methylpentan-2-one
	111-76-2	2-butoxyethanol
	123-86-4	n-Butyl acetate
	1330-20-7	Xylene
PA	1333-86-4	carbon black
	100-41-4	ethylbenzene
	108-10-1	4-methylpentan-2-one
	111-76-2	2-butoxyethanol
	123-86-4	n-Butyl acetate
	1330-20-7	Xylene
	1333-86-4	carbon black

#### **Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:**

**WARNING:** This product can expose you to chemicals including METHYL ISOBUTYL KETONE (MIBK), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

##### **NFPA Hazard codes:**

Health: 2 Fire: 3 Reactivity: 0 Special:

##### **HMIS III rating**

Health: 2 $\frac{1}{2}$  Flammability: 3 Physical hazard: 0

### 16. Other Information

##### **SDS Prepared by:**

BASF NA Product Regulations

SDS Prepared on: 2023/05/18

# Safety Data Sheet

## 35-M1910 Black Yellow

Revision date: 2023/05/18

Version: 8.0

Page: 14/14

(30779253/SDS\_GEN\_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET