

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 1/13  
(30089157/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## LB303 YELLOW SHADE GREEN

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
5025 Creekbank Road  
Building A, Floor 2  
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

##### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Carc.	1	Carcinogenicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 2/13

(30089157/SDS\_GEN\_CA/EN)

Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
STOT RE	2	Specific target organ toxicity — repeated exposure

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Kidney, Central nervous system, Liver, Auditory organ) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 3/13

(30089157/SDS\_GEN\_CA/EN)

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.
P308 + P313	IF exposed or concerned: Get medical attention.
P314	Get medical advice/attention if you feel unwell.

### Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

### Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### 1,2,4-trimethylbenzene

CAS Number: 95-63-6  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: 1,2,4-Trimethylbenzene

#### butanone oxime

CAS Number: 96-29-7  
Content (W/W):  $\geq 0.2$  -  $< 0.3\%$   
Synonym: 2-Butanone, oxime; Methyl ethyl ketoxime

#### cumene

CAS Number: 98-82-8  
Content (W/W):  $\geq 0.2$  -  $< 0.3\%$   
Synonym: (1-Methylethyl)benzene; Isopropylbenzene, Cumene

#### ethylbenzene

CAS Number: 100-41-4  
Content (W/W):  $\geq 7.0$  -  $< 10.0\%$   
Synonym: Ethylbenzene

#### Xylene

CAS Number: 1330-20-7  
Content (W/W):  $\geq 25.0$  -  $< 50.0\%$   
Synonym: Xylene; Dimethylbenzene

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 4/13  
(30089157/SDS\_GEN\_CA/EN)

Benzene, trimethyl-  
CAS Number: 25551-13-7  
Content (W/W):  $\geq 1.0 - < 3.0\%$   
Synonym: Trimethylbenzene

Solvent naphtha (petroleum), light arom.  
CAS Number: 64742-95-6  
Content (W/W):  $\geq 3.0 - < 5.0\%$   
Synonym: No data available.

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: 1,2,4-trimethylbenzene*

*Symptoms: Overexposure may cause:, headache, tiredness, nausea, anxiety, asthma, bronchitis, noncardiogenic pulmonary edema*

*Information on: butanone oxime*

*Symptoms: Overexposure may cause:, corneal injury, skin corrosion, coughing, respiratory disorders, dyspnea, nausea, vomiting, diarrhea*

*Information on: cumene*

*Symptoms: Overexposure may cause:, unconsciousness, coordination disorder, headache, dizziness*

*Information on: Xylene*

*Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness*

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 5/13  
(30089157/SDS\_GEN\_CA/EN)

*Information on: Benzene, trimethyl-*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:, irritation of respiratory tract, coughing*

*Information on: Solvent naphtha (petroleum), light arom.*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death*  
-----

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 6/13

(30089157/SDS\_GEN\_CA/EN)

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

Benzene	ACGIH, US:	STEL value 2.5 ppm ;
	ACGIH, US:	TWA value 0.5 ppm ;
	OSHA Z2:	max. conc. 50 ppm ;
	OSHA Z2:	CLV 25 ppm ;
	OSHA Z2:	TWA value 10 ppm ;
	OSHA, US:	TWA value 1 ppm ;
	OSHA, US:	OSHA Action level 0.5 ppm ;
	OSHA, US:	STEL value 5 ppm ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
1,2,4-trimethylbenzene	ACGIH, US:	TWA value 25 ppm ;

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 7/13

(30089157/SDS\_GEN\_CA/EN)

cumene	OSHA Z1:	Skin Designation ; The substance can be absorbed through the skin.
	OSHA Z1:	PEL 50 ppm 245 mg/m3 ;
	ACGIH, US:	TWA value 5 ppm ;
ethylbenzene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
Xylene	ACGIH, US:	TWA value 100 ppm ;
	ACGIH, US:	STEL value 150 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
Benzene, trimethyl-	ACGIH, US:	TWA value 25 ppm ;

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid
Odour:	aromatic
Odour threshold:	No applicable information available.
Colour:	green
pH value:	No applicable information available.
Melting point:	No applicable information available.
Freezing point:	No applicable information available.
Boiling range:	136.67 - 171.00 °C
Sublimation point:	No applicable information available.
Flash point:	23.00 °C
Flammability:	No applicable information available.
Lower explosion limit:	0.90 %(V)

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 8/13

(30089157/SDS\_GEN\_CA/EN)

Upper explosion limit:	7.00 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.0143 g/cm3 ( 20 °C)	(calculated)
Relative density:	1.0143 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.500 mm2/s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 9/13  
(30089157/SDS\_GEN\_CA/EN)

### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

#### *Information on: 1,2,4-trimethylbenzene*

*Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.*

#### *Information on: butanone oxime*

*Assessment of acute toxicity: Of pronounced toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Of moderate toxicity after short-term skin contact. EU-classification*

#### *Information on: cumene*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.*

#### *Information on: ethylbenzene*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.*

#### *Information on: Xylene*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.*

#### *Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of acute toxicity: Virtually nontoxic after a single ingestion. No deaths at the highest dose tested after short-term inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Of low toxicity after short-term skin contact.*

### Oral

Type of value: LD50

Species: rat

Value:  $\geq 3,400.00000$  mg/kg

### Inhalation

Type of value: LC50

Species: rat

Value: 17.200000 mg/l

### Dermal

Type of value: LD50

Species: rabbit

Value:  $> 4,300.000000$  mg/kg

### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 10/13  
(30089157/SDS\_GEN\_CA/EN)

*Information on: 1,2,4-trimethylbenzene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: butanone oxime*

*Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes irritation.*

*Information on: cumene*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes. Causes temporary irritation of the respiratory tract.*

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

*Information on: butanone oxime*

*Assessment of sensitization:  
Sensitization after skin contact possible.*

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

*Information on: Xylene*

*Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion.*

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 11/13

(30089157/SDS\_GEN\_CA/EN)

*Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

*Information on: butanone oxime*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.*

*Information on: cumene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

*Information on: Xylene*

*Assessment of teratogenicity: In animal studies the substance did not cause malformations.*

-----

*Information on: butanone oxime*

*Assessment of teratogenicity: Based on available data, the classification criteria are not met.*

-----

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life with long lasting effects. Toxic to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

### Additional information

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18

Version: 4.0

Page: 12/13  
(30089157/SDS\_GEN\_CA/EN)

Other ecotoxicological advice:  
Acutely toxic for aquatic organisms.

### 13. Disposal considerations

#### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

#### Container disposal:

WARNING: Empty containers may still contain hazardous residue.

### 14. Transport Information

#### Land transport

TDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

#### Sea transport

IMDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: PAINT

#### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

### 15. Regulatory Information

#### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

# Safety Data Sheet

## LB303 YELLOW SHADE GREEN

Revision date : 2022/03/18  
Version: 4.0

Page: 13/13  
(30089157/SDS\_GEN\_CA/EN)

---

### 16. Other Information

**SDS Prepared by:**  
BASF NA Product Regulations  
SDS Prepared on: 2022/03/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET