



We create chemistry

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 1/13

(30647896/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## LOP30 Primer Surfacer

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
5025 Creekbank Road  
Building A, Floor 2  
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 2/13

(30647896/SDS\_GEN\_CA/EN)

Aquatic Chronic  
Flam. Liq.

2  
3

Hazardous to the aquatic environment - chronic  
Flammable liquids

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H373	May cause damage to organs (Central nervous system, Auditory organ, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P260	Do not breathe dust or mist.
P240	Ground and bond container and receiving equipment.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P280	Wear protective gloves, protective clothing and eye protection or face protection.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P391	Collect spillage.
P314	Get medical advice/attention if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370 + P378	In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21  
Version: 4.0

Page: 3/13  
(30647896/SDS\_GEN\_CA/EN)

### 3. Composition / Information on Ingredients

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

##### ethylbenzene

CAS Number: 100-41-4  
Content (W/W):  $\geq 1.0 - < 3.0\%$   
Synonym: Ethylbenzene

##### 1-methoxy-2-propylacetate

CAS Number: 108-65-6  
Content (W/W):  $\geq 3.0 - < 5.0\%$   
Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

##### n-Butyl acetate

CAS Number: 123-86-4  
Content (W/W):  $\geq 20.0 - < 25.0\%$   
Synonym: n-Butyl acetate

##### Magnesium carbonate

CAS Number: 546-93-0  
Content (W/W):  $\geq 5.0 - < 7.0\%$   
Synonym: Magnesium carbonate

##### Propanoic acid, 3-ethoxy-, ethyl ester

CAS Number: 763-69-9  
Content (W/W):  $\geq 3.0 - < 5.0\%$   
Synonym: 3-Ethoxypropanoic acid ethyl ester; Ethyl 3-ethoxypropionate

##### Xylene

CAS Number: 1330-20-7  
Content (W/W):  $\geq 5.0 - < 7.0\%$   
Synonym: Xylene; Dimethylbenzene

##### Barium sulfate

CAS Number: 7727-43-7  
Content (W/W):  $\geq 10.0 - < 15.0\%$   
Synonym: Barium sulfate, natural

##### zinc phosphate

CAS Number: 7779-90-0  
Content (W/W):  $\geq 5.0 - < 7.0\%$   
Synonym: Trizinc bis(orthophosphate)

##### Titanium dioxide

CAS Number: 13463-67-7  
Content (W/W):  $\geq 10.0 - < 15.0\%$   
Synonym: C.I. Pigment White 6

##### talc

CAS Number: 14807-96-6  
Content (W/W):  $\geq 7.0 - < 10.0\%$   
Synonym: hydrated magnesium silicate

##### Solvent naphtha (petroleum), light arom.

CAS Number: 64742-95-6  
Content (W/W):  $\geq 1.0 - < 3.0\%$

# Safety Data Sheet

## LOP30 Primer Surfacers

Revision date : 2022/03/21

Version: 4.0

Page: 4/13

(30647896/SDS\_GEN\_CA/EN)

Synonym: No data available.

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

##### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

##### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

#### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: Magnesium carbonate*

*Symptoms: No data available.*

*Information on: Propanoic acid, 3-ethoxy-, ethyl ester*

*Symptoms: Overexposure may cause:, unconsciousness, vomiting, lethargy, nausea, headache, dizziness*

*Information on: Xylene*

*Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness*

*Information on: zinc phosphate*

*Symptoms: No data available.*

*Information on: talc*

*Symptoms: Overexposure may cause:, vomiting, convulsions, cyanosis, irregular breathing, dyspnea*

*Information on: Solvent naphtha (petroleum), light arom.*

*Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death*

#### Indication of any immediate medical attention and special treatment needed

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 5/13

(30647896/SDS\_GEN\_CA/EN)

### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

# Safety Data Sheet

## LOP30 Primer Surfacers

Revision date : 2022/03/21

Version: 4.0

Page: 6/13

(30647896/SDS\_GEN\_CA/EN)

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

ethylbenzene	ACGIH, US: OSHA Z1:	TWA value 20 ppm ; PEL 100 ppm 435 mg/m3 ;
n-Butyl acetate	ACGIH, US: ACGIH, US: OSHA Z1:	STEL value 150 ppm ; TWA value 50 ppm ; PEL 150 ppm 710 mg/m3 ;
Magnesium carbonate	OSHA Z1: OSHA Z1: ACGIH, US: ACGIH, US: OSHA Z3:  OSHA Z3: OSHA Z3: OSHA Z3:	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 3 mg/m3 Respirable particles ; TWA value 10 mg/m3 Inhalable particles ; TWA value 15 millions of particles per cubic foot of air Respirable fraction ; TWA value 5 mg/m3 Respirable fraction ; TWA value 50 millions of particles per cubic foot of air Total dust ; TWA value 15 mg/m3 Total dust ;
Xylene	ACGIH, US: ACGIH, US: OSHA Z1:	TWA value 100 ppm ; STEL value 150 ppm ; PEL 100 ppm 435 mg/m3 ;
carbon black	ACGIH, US: OSHA Z1:	TWA value 3 mg/m3 Inhalable fraction ; PEL 3.5 mg/m3 ;

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 7/13

(30647896/SDS\_GEN\_CA/EN)

Barium sulfate	ACGIH, US:	TWA value 5 mg/m3 Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
	OSHA Z1:	PEL 15 mg/m3 Total dust ;
	OSHA Z1:	PEL 5 mg/m3 Respirable fraction ;
Titanium dioxide	ACGIH, US:	TWA value 10 mg/m3 ;
	OSHA Z1:	PEL 15 mg/m3 Total dust ;
talc	ACGIH, US:	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
	OSHA Z3:	TWA value 20 millions of particles per cubic foot of air ;
	OSHA Z3:	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	OSHA Z3:	TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10mg/m^3/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### Body protection:

Body protection must be chosen based on level of activity and exposure.

#### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

---

## 9. Physical and Chemical Properties

Form: liquid

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 8/13

(30647896/SDS\_GEN\_CA/EN)

Odour:	No data available.	
Odour threshold:	No applicable information available.	
Colour:	grey	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	124.00 - 3,000.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	27.22 °C	
Flammability:	No applicable information available.	
Lower explosion limit:	1.40 %(V)	
Upper explosion limit:	7.60 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	1.4361 g/cm3 ( 20 °C)	(calculated)
Relative density:	1.4361 ( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.500 mm2/s	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.



# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 9/13

(30647896/SDS\_GEN\_CA/EN)

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

##### *Information on: ethylbenzene*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.*

##### *Information on: Propanoic acid, 3-ethoxy-, ethyl ester*

*Assessment of acute toxicity: Of low toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Of low toxicity after short-term skin contact.*

##### *Information on: Xylene*

*Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.*

##### *Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of acute toxicity: Virtually nontoxic after a single ingestion. No deaths at the highest dose tested after short-term inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Of low toxicity after short-term skin contact.*

#### Oral

Type of value: LD50

Species: rat

Value: 3,500.000000 mg/kg

#### Inhalation

Type of value: LC50

Species: rat

Value: 2.300000 mg/l

#### Dermal

Type of value: LD50

Species: rabbit

Value: > 4,300.000000 mg/kg

#### Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

# Safety Data Sheet

## LOP30 Primer Surfacers

Revision date : 2022/03/21

Version: 4.0

Page: 10/13

(30647896/SDS\_GEN\_CA/EN)

### Irritation / corrosion

Assessment of irritating effects: Based on available data, the classification criteria are not met.

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: n-Butyl acetate*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.  
Not irritating to the skin. May cause slight irritation to the eyes.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

*Information on: 1-methoxy-2-propylacetate*

*Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.*

*Information on: n-Butyl acetate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

*Information on: Xylene*

*Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney*

*Information on: Barium sulfate*

*Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.*

*Information on: Titanium dioxide*

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 11/13

(30647896/SDS\_GEN\_CA/EN)

*Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion.*

*Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

---

## 12. Ecological Information

### **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

Toxic to aquatic life. Toxic to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

---

## 13. Disposal considerations

**Waste disposal of substance:**

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 12/13

(30647896/SDS\_GEN\_CA/EN)

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

### Container disposal:

WARNING: Empty containers may still contain hazardous residue.

---

## 14. Transport Information

### Land transport

TDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

### Sea transport

IMDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: PAINT

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

---

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2022/03/21

# Safety Data Sheet

## LOP30 Primer Surfacer

Revision date : 2022/03/21

Version: 4.0

Page: 13/13

(30647896/SDS\_GEN\_CA/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET