

# Safety Data Sheet

## LB520 DARK MAROON

Revision date : 2023/11/10  
Version: 7.0

Page: 1/13  
(30089161/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

**LB520 DARK MAROON**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
5025 Creekbank Road  
Building A, Floor 2  
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Carc.	1	Carcinogenicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10

Version: 7.0

Page: 2/13

(30089161/SDS\_GEN\_CA/EN)

Flam. Liq.	3
Aquatic Acute	2
Aquatic Chronic	3
STOT RE	2

Flammable liquids  
Hazardous to the aquatic environment - acute  
Hazardous to the aquatic environment - chronic  
Specific target organ toxicity — repeated exposure

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Liver, Auditory organ, Lung, Respiratory system, Central nervous system, Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P201	Obtain special instructions before use.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P240	Ground and bond container and receiving equipment.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash contaminated body parts thoroughly after handling.
P260	Do not breathe mist or vapour or spray.

Precautionary Statements (Response):

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 3/13  
(30089161/SDS\_GEN\_CA/EN)

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332 + P313	If skin irritation occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use water spray for extinction.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

### Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

### Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Xylene

CAS Number: 1330-20-7  
Content (W/W):  $\geq 25.0$  -  $< 50.0\%$   
Synonym: Xylene; Dimethylbenzene

#### ethylbenzene

CAS Number: 100-41-4  
Content (W/W):  $\geq 5.0$  -  $< 7.0\%$   
Synonym: Ethylbenzene

#### Solvent naphtha (petroleum), light arom.

CAS Number: 64742-95-6  
Content (W/W):  $\geq 5.0$  -  $< 7.0\%$   
Synonym: No data available.

#### Anthra[2,1,9-def:6,5,10-d'e'f']diisoquinoline-1,3,8,10(2H,9H)- tetrone, 2,9-dimethyl-

CAS Number: 5521-31-3  
Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: Anthra[2,1,9-def:6,5,10-d'e'f']diisoquinoline-1,3,8,10(2H,9H)-tetrone, 2,9-dimethyl-

#### Benzene, trimethyl-

CAS Number: 25551-13-7

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 4/13  
(30089161/SDS\_GEN\_CA/EN)

Content (W/W):  $\geq 3.0$  -  $< 5.0\%$   
Synonym: Trimethylbenzene

1,2,4-trimethylbenzene  
CAS Number: 95-63-6  
Content (W/W):  $\geq 1.0$  -  $< 3.0\%$   
Synonym: 1,2,4-Trimethylbenzene

butanone oxime  
CAS Number: 96-29-7  
Content (W/W):  $\geq 0.3$  -  $< 1.0\%$   
Synonym: 2-Butanone, oxime; Methyl ethyl ketoxime

cumene  
CAS Number: 98-82-8  
Content (W/W):  $\geq 0.2$  -  $< 0.3\%$   
Synonym: (1-Methylethyl)benzene; Isopropylbenzene, Cumene

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

#### If on skin:

If irritation develops, seek medical attention. Seek medical attention. Wash affected areas with water for at least 15 minutes. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed. Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

#### If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

*Information on: 1,2,4-trimethylbenzene*

*Symptoms: Overexposure may cause: headache, tiredness, nausea, anxiety, asthma, bronchitis, noncardiogenic pulmonary edema*

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 5/13  
(30089161/SDS\_GEN\_CA/EN)

*Information on: butanone oxime*

*Symptoms: Overexposure may cause:; corneal injury, skin corrosion, coughing, respiratory disorders, dyspnea, nausea, vomiting, diarrhea*

*Information on: cumene*

*Symptoms: Overexposure may cause:; unconsciousness, coordination disorder, headache, dizziness*

*Information on: ethylbenzene*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, irritation of the mucous membranes, erythema, nausea, headache, dizziness, diarrhea, abdominal cramps, dermatitis, loss of hearing, Ingestion may provoke the following symptoms:; asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse*

*Information on: Xylene*

*Symptoms: Overexposure may cause:; coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness*

*Information on: Benzene, trimethyl-*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:; irritation of respiratory tract, coughing*

*Information on: Solvent naphtha (petroleum), light arom.*

*Symptoms: Overexposure may cause:; Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:; asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death*

-----  
Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

Suitable extinguishing media:

carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 6/13  
(30089161/SDS\_GEN\_CA/EN)

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Store in a well-ventilated place. Keep cool. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed. Store protected against freezing. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.  
Protect from temperatures above: 49 °C

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 7/13  
(30089161/SDS\_GEN\_CA/EN)

Benzene	ACGIH, US:	STEL value 2.5 ppm ;
	OSHA Z2:	max. conc. 50 ppm ;
	OSHA Z2:	CLV 25 ppm ;
	OSHA Z2:	TWA value 10 ppm ;
	OSHA, US:	TWA value 1 ppm ;
	OSHA, US:	OSHA Action level 0.5 ppm ;
	OSHA, US:	STEL value 5 ppm ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
1,2,4-trimethylbenzene	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	TWA value 0.05 ppm ;
	ACGIH, US:	TWA value 0.5 ppm ;
cumene	ACGIH, US:	TWA value 10 ppm ;
ethylbenzene	OSHA Z1:	Skin Designation ; The substance can be absorbed through the skin.
	OSHA Z1:	PEL 50 ppm 245 mg/m3 ;
	ACGIH, US:	TWA value 5 ppm ;
Xylene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
Benzene, trimethyl-	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
	ACGIH, US:	TWA value 20 ppm ;
Benzene, trimethyl-	ACGIH, US:	TWA value 25 ppm ;
	ACGIH, US:	TWA value 10 ppm ;

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

#### Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10

Version: 7.0

Page: 8/13

(30089161/SDS\_GEN\_CA/EN)

### Body protection:

Body protection must be chosen based on level of activity and exposure.

### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing.

Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	aromatic	
Odour threshold:	No applicable information available.	
Colour:	maroon	
pH value:	No applicable information available.	
	substance/mixture is non-polar/aprotic	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	136 - 146 °C	
Sublimation point:	No applicable information available.	
Flash point:	23 °C	(ASTM D3278)
Flammability:	The product burns self-sustainingly	
	No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	7.00 %(V)	
Autoignition:	No applicable information available.	
Vapour pressure:	8.00 hPa	
	( 20 °C)	
	37.00 hPa	
	( 50 °C)	
Density:	1.014 g/cm3	
	( 20 °C)	
Relative density:	1.0135	
	( 20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	20.7 mm2/s	
	( 23 °C)	
	( 40 °C)	
	No data available.	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	



# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 9/13  
(30089161/SDS\_GEN\_CA/EN)

### 10. Stability and Reactivity

#### Reactivity

No applicable information available.

#### Chemical stability

The product is chemically stable.

#### Possibility of hazardous reactions

No applicable information available.

#### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

#### Incompatible materials

strong oxidizing agents, strong bases, strong acids

#### Hazardous decomposition products

Decomposition products:

nitrogen oxides, carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

##### Oral

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

##### Inhalation

Type of value: ATE

Value: 130 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

##### Dermal

Type of value: ATE

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10

Version: 7.0

Page: 10/13

(30089161/SDS\_GEN\_CA/EN)

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

*Information on: 1,2,4-trimethylbenzene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: butanone oxime*

*Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes irritation. EU-classification*

*Information on: cumene*

*Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.*

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: Benzene, trimethyl-*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation. EU-classification The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

*Information on: butanone oxime*

*Assessment of sensitization:*

*Sensitization after skin contact possible. EU-classification*

### Aspiration Hazard

No aspiration hazard expected.

## Chronic Toxicity/Effects

### Repeated dose toxicity

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 11/13  
(30089161/SDS\_GEN\_CA/EN)

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

*Information on: butanone oxime*

*Assessment of repeated dose toxicity: Repeated exposure may affect certain organs. EU-classification*

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

*Information on: Xylene*

*Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity. Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney*

*Information on: Solvent naphtha (petroleum), light arom.*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated ingestion. Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

-----

### Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

*Information on: butanone oxime*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. EU-classification*

*Information on: cumene*

*Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 12/13  
(30089161/SDS\_GEN\_CA/EN)

Information on: Xylene

Assessment of teratogenicity: In animal studies the substance did not cause malformations.

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life with long lasting effects. Toxic to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

### Additional information

Other ecotoxicological advice:

Acutely toxic for aquatic organisms.

---

## 13. Disposal considerations

### Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

### Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

---

## 14. Transport Information

### Land transport

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

### Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

# Safety Data Sheet

## LB520 DARK MAROON

Revision date: 2023/11/10  
Version: 7.0

Page: 13/13  
(30089161/SDS\_GEN\_CA/EN)

### Air transport

IATA/ICAO  
Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

#### NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 0 Special:

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2023/11/10

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET