

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25

Version: 3.0

Page: 1/11

(30091104/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## Q995 SCHOOL BUS YELLOW

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial use only

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: Coating

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

#### Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2B	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Muta.	1	Germ cell mutagenicity
Carc.	1	Carcinogenicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids
Aquatic Acute	2	Hazardous to the aquatic environment - acute

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25

Version: 3.0

Page: 2/11

(30091104/SDS\_GEN\_CA/EN)

Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
STOT RE	2	Specific target organ toxicity — repeated exposure
STOT RE	2	Specific target organ toxicity — repeated exposure
STOT RE	2	Specific target organ toxicity — repeated exposure
STOT RE	2	Specific target organ toxicity — repeated exposure

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H320	Causes eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.
H226	Flammable liquid and vapour.
H373	May cause damage to organs (Auditory organ, Central nervous system, Kidney, Liver) through prolonged or repeated exposure.
H335	May cause respiratory irritation.
H350	May cause cancer.
H340	May cause genetic defects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P264	Wash with plenty of water and soap thoroughly after handling.
P281	Use personal protective equipment as required.
P271	Use only outdoors or in a well-ventilated area.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P243	Take precautionary measures against static discharge.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust or mist.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 3/11  
(30091104/SDS\_GEN\_CA/EN)

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P363	Wash contaminated clothing before reuse.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P321	Specific treatment (see on this label).
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.

#### Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

#### Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

### According to Controlled Products Regulations (CPR) (SOR/88-66)

#### Emergency overview

Skin and/or eye irritant  
CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE.  
INGESTION MAY CAUSE GASTRIC DISTURBANCES.  
May cause pulmonary edema.  
FLAMMABLE LIQUID.  
HARMFUL IF INHALED.  
CONTAINS A MATERIAL WHICH HAS BEEN IDENTIFIED AS A SUSPECT CANCER HAZARD.

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
96-29-7	>= 0.3 - < 1.0%	butanone oxime
100-41-4	>= 3.0 - < 5.0%	ethylbenzene
1330-20-7	>= 25.0 - < 50.0%	Xylene
64742-95-6	>= 1.0 - < 3.0%	solvent naphtha
13463-67-7	>= 1.0 - < 3.0%	Titanium dioxide
7789-82-4	>= 1.0 - < 3.0%	Molybdate (MoO42-), calcium (1:1), (T-4)-

### According to Controlled Products Regulations (CPR) (SOR/88-66)

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 4/11  
(30091104/SDS\_GEN\_CA/EN)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
100-41-4	2.589 %	ethylbenzene
1330-20-7	32.8044 %	Xylene
13463-67-7	0.9642 %	Titanium dioxide

---

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

##### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

##### If in eyes:

Flush with copious amounts of water for at least 15 minutes. If irritation develops, seek medical attention. Seek medical attention.

##### If swallowed:

Immediate medical attention required. Do not induce vomiting due to aspiration hazard. Rinse mouth and then drink plenty of water.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 5/11  
(30091104/SDS\_GEN\_CA/EN)

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

### Environmental precautions

Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

---

## 7. Handling and Storage

### Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

### Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 6/11  
(30091104/SDS\_GEN\_CA/EN)

ethylbenzene	OSHA PEL	PEL 100 ppm 435 mg/m3 ; STEL value 125 ppm 545 mg/m3 ; TWA value 100 ppm 435 mg/m3 ; PEL 100 ppm 435 mg/m3 ; TWA value 100 ppm 435 mg/m3 ; STEL value 125 ppm 545 mg/m3 ;
	ACGIH TLV	TWA value 20 ppm ; TWA value 20 ppm ;
Xylene	OSHA PEL	PEL 100 ppm 435 mg/m3 ; STEL value 150 ppm 655 mg/m3 ; TWA value 100 ppm 435 mg/m3 ;
	ACGIH TLV	TWA value 100 ppm ; STEL value 150 ppm ;
Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
Molybdate (MoO42-), calcium (1:1), (T-4)-	OSHA PEL	PEL 5 mg/m3 (molybdenum (Mo));
	ACGIH TLV	TWA value 0.5 mg/m3 Respirable fraction (molybdenum (Mo));

### Personal protective equipment

#### **Respiratory protection:**

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

#### **Hand protection:**

Chemical resistant protective gloves

#### **Eye protection:**

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

#### **General safety and hygiene measures:**

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Contaminated equipment or clothing should be cleaned after each use or disposed of. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

---

## 9. Physical and Chemical Properties

Form:	liquid
Odour:	moderate odour
Odour threshold:	No applicable information available.
Colour:	No applicable information available.
pH value:	Unspecified
Melting point:	No applicable information available.
Boiling range:	136.67 - 180.00 °C
Sublimation point:	No applicable information available.
Flash point:	23.00 °C
Flammability:	No applicable information available.
Lower explosion limit:	0.90 %(V)
Upper explosion limit:	7.00 %(V)

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 7/11  
(30091104/SDS\_GEN\_CA/EN)

Density:	9.0569 lb/USg ( 20 °C)	(calculated)
Relative density:	1.0853	(calculated)
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
% volatiles:	dry	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	No applicable information available.	

## 10. Stability and Reactivity

### Reactivity

No applicable information available.

### Chemical stability

The product is chemically stable.

### Possibility of hazardous reactions

No applicable information available.

### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

### Incompatible materials

strong oxidizing agents, strong bases, strong acids

### Hazardous decomposition products

Decomposition products:  
carbon dioxide, carbon monoxide

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Primary routes of entry

Solvents are absorbed through the skin.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

#### *Information on: butanone oxime*

*Assessment of acute toxicity: Of moderate toxicity after short-term skin contact. In animal studies the substance is virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.*

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 8/11  
(30091104/SDS\_GEN\_CA/EN)

*Information on: ethylbenzene*

*Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.*

-----

### Oral

Type of value: LD50

Species: rat

Value: 3,500.000000 mg/kg

### Inhalation

Type of value: LC50

Species: rat

Value: > 5.000000 mg/l

### Dermal

Type of value: LD50

Species: rabbit

Value: > 2,000.000000 mg/kg

### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

*Information on: butanone oxime*

*Assessment of irritating effects: May cause severe damage to the eyes. Not irritating to the skin.*

*Information on: Xylene*

*Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.*

*Information on: solvent naphtha*

*Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: ethylbenzene*

*Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.*

-----

### Sensitization

*Information on: butanone oxime*

*Assessment of sensitization:*

*Sensitization after skin contact possible.*

-----

### Aspiration Hazard

No applicable information available.

## Chronic Toxicity/Effects

### Repeated dose toxicity

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 9/11  
(30091104/SDS\_GEN\_CA/EN)

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

*Information on: butanone oxime*

*Information on: ethylbenzene*

*Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.*

*Information on: Titanium dioxide*

*Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.*

### Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

*Information on: butanone oxime*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.*

*Information on: ethylbenzene*

*Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). NTP listed carcinogen*

*Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

### Teratogenicity

*Information on: Xylene*

*Assessment of teratogenicity: In animal studies the substance did not cause malformations.*

## Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## 12. Ecological Information

No applicable information available.

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 10/11  
(30091104/SDS\_GEN\_CA/EN)

### 13. Disposal considerations

**Waste disposal of substance:**

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

**Container disposal:**

WARNING: Empty containers may still contain hazardous residue.

### 14. Transport Information

**Land transport**

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

**Sea transport**

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

**Air transport**

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

### 15. Regulatory Information

**VOC content:**

3.782338 lb/US-gal  
dry

**Federal Regulations****Registration status:**

Chemical                      DSL, CA              released / listed

**According to Controlled Products Regulations (CPR) (SOR/88-66)**

# Safety Data Sheet

## Q995 SCHOOL BUS YELLOW

Revision date : 2016/02/25  
Version: 3.0

Page: 11/11  
(30091104/SDS\_GEN\_CA/EN)

### WHMIS classification:

B2: Flammable Liquid



D2A: Materials Causing Other Toxic Effects - Very toxic material



D2B: Materials Causing Other Toxic Effects - Toxic material



**THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.**

## 16. Other Information

**SDS Prepared by:**  
BASF NA Product Regulations  
SDS Prepared on: 2016/02/25

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET