



We create chemistry

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18
Version: 5.0

Page: 1/12
(30437532/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

LA20 EPOXY PRIMER ACTIVATOR

Recommended use of the chemical and restriction on use

Recommended use*: hardener

Recommended use*: Paints, Coatings and Related Materials; for industrial use only

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: Coating

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Skin Corr./Irrit.

2

Eye Dam./Irrit.

1

Flam. Liq.

3

Aquatic Acute

3

Skin corrosion/irritation

Serious eye damage/eye irritation

Flammable liquids

Hazardous to the aquatic environment - acute

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 2/12

(30437532/SDS_GEN_CA/EN)

Acute Tox.	4 (oral)	Acute toxicity
STOT RE	2	Specific target organ toxicity — repeated exposure
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H373	May cause damage to organs (Auditory organ, Kidney, Liver, Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use only non-sparking tools.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P240	Ground and bond container and receiving equipment.
P270	Do not eat, drink or smoke when using this product.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 3/12

(30437532/SDS_GEN_CA/EN)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P370 + P378 In case of fire: Use water spray for extinction.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P330 Rinse mouth
P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P314 Get medical advice/attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical attention.
P310 Immediately call a POISON CENTER or physician.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

n-butanol

CAS Number: 71-36-3
Content (W/W): ≥ 3.0 - $< 5.0\%$
Synonym: 1-Butanol; n-Butanol

ethylbenzene

CAS Number: 100-41-4
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: Ethylbenzene

Benzyl alcohol

CAS Number: 100-51-6
Content (W/W): ≥ 3.0 - $< 5.0\%$
Synonym: Benzyl alcohol

ethylenediamine

CAS Number: 107-15-3
Content (W/W): ≥ 0.2 - $< 0.3\%$
Synonym: 1,2-Ethanediamine; Ethylenediamine

2-heptanone

CAS Number: 110-43-0
Content (W/W): ≥ 25.0 - $< 50.0\%$
Synonym: 2-Heptanone; Methyl n-amyl ketone

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18
Version: 5.0

Page: 4/12
(30437532/SDS_GEN_CA/EN)

Xylene

CAS Number: 1330-20-7
Content (W/W): ≥ 10.0 - $< 15.0\%$
Synonym: Xylene; Dimethylbenzene

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Seek medical attention. Immediately wash affected area with soap and water for 20-30 minutes or until chemical is removed.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention. Seek medical attention.

If swallowed:

Immediate medical attention required. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting. Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: n-butanol

Symptoms: Overexposure may cause:, headache, dizziness, coordination disorder, coma, lacrimation, loss of hearing

Information on: Benzyl alcohol

Symptoms: Overexposure may cause:, vomiting, dizziness, nausea, diarrhea

Information on: ethylenediamine

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: 2-heptanone

Symptoms: Overexposure may cause:, headache, dizziness, nausea, unconsciousness

Information on: Xylene

Symptoms: Overexposure may cause:, coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18
Version: 5.0

Page: 5/12
(30437532/SDS_GEN_CA/EN)

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Vapors and/or decomposition products are irritant and/or toxic. If product is heated above decomposition temperature acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Notify proper authorities. Do not flood burning material with water due to potential spreading of fire. Flash fire may occur. Run-off water from fire may cause pollution. Contain contaminated water/firefighting water. Remove product from areas of fire, or otherwise cool sealed containers with water in order to avoid pressure build up due to heat. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Use antistatic tools. Extinguish sources of ignition nearby and downwind. Avoid prolonged inhalation. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Dike spillage. Spills should be contained, solidified, and placed in suitable containers for disposal. Place into appropriately labeled waste containers.

7. Handling and Storage

Precautions for safe handling

Handle and open container with care. WARNING: Empty containers may still contain hazardous residue. Use static lines when mixing and transferring material. Do not puncture, drop, or slide containers. Ensure adequate ventilation. Avoid contact with the skin, eyes and clothing.

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 6/12

(30437532/SDS_GEN_CA/EN)

Protection against fire and explosion:

Risk of explosion if heated under confinement. Use antistatic tools. Exhaust fans should be explosion proof. Avoid all sources of ignition: heat, sparks, open flame. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up.

Conditions for safe storage, including any incompatibilities

Segregate from strong bases. Segregate from oxidizing agents. Segregate from incompatible substances. Segregate from strong acids.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), Stove lacquer Valspar 36516AA, Stove-lacquer KNS L-5X

Further information on storage conditions: Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Consult local fire marshal for storage requirements.

Protect from temperatures above: 49 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

n-butanol	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 300 mg/m3 ;
ethylbenzene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;
ethylenediamine	ACGIH, US:	TWA value 10 ppm ;
	OSHA Z1:	PEL 10 ppm 25 mg/m3 ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
2-heptanone	ACGIH, US:	TWA value 50 ppm ;
	OSHA Z1:	PEL 100 ppm 465 mg/m3 ;
Xylene	ACGIH, US:	TWA value 100 ppm ;
	ACGIH, US:	STEL value 150 ppm ;
	OSHA Z1:	PEL 100 ppm 435 mg/m3 ;

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

Respiratory protection may not be required under normal operating conditions if adequate ventilation

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 7/12

(30437532/SDS_GEN_CA/EN)

is provided. Wear a NIOSH-certified (or equivalent) organic vapour respirator. Particulate filters should be added during spray operations. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Use appropriate chemically impervious gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Wear face shield if splashing hazard exists. Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Remove contaminated clothing. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Contact lenses should not be worn. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	No data available.	
Odour threshold:	No applicable information available.	
Colour:	pale straw yellow	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling range:	66.00 - 152.00 °C	
Sublimation point:	No applicable information available.	
Flash point:	35 °C	
Flammability:	No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	0.9062 g/cm ³ (20 °C)	(calculated)
Relative density:	0.9062 (20 °C)	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	> 20.500 mm ² /s	
Solubility in water:	No applicable information available.	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molar mass:	No applicable information available.	
Evaporation rate:	No applicable information available.	

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 8/12

(30437532/SDS_GEN_CA/EN)

10. Stability and Reactivity

Reactivity

No applicable information available.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No applicable information available.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion.

Information on: n-butanol

Assessment of acute toxicity: Of low toxicity after short-term skin contact. Virtually nontoxic by inhalation. Of low toxicity after single ingestion. The European Union (EU) has classified this substance as 'harmful' after oral exposure.

If used as intended, this product is not expected to present a physical or health hazard.

Information on: ethylbenzene

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. Of low toxicity after single ingestion.

Information on: Benzyl alcohol

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of moderate toxicity after short-term inhalation.

May cause central nervous system effects.

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 9/12

(30437532/SDS_GEN_CA/EN)

Information on: ethylenediamine

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term skin contact. Of moderate toxicity after short-term inhalation.

Information on: 2-heptanone

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of moderate toxicity after single ingestion. Virtually nontoxic after a single skin contact.

Information on: Xylene

Assessment of acute toxicity: Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.

Oral

No applicable information available.

Type of value: LD50

Species: rat

Value: 1,610.000000 mg/kg

Inhalation

No applicable information available.

Type of value: LC50

Species: rat

Value: > 4.100000 mg/l

Dermal

No applicable information available.

Type of value: LD50

Species: rabbit

Value: 2,000.000000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: n-butanol

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Information on: ethylbenzene

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: Benzyl alcohol

Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation. An in vitro test indicated the potential to cause serious damage to the eyes.

Information on: ethylenediamine

Assessment of irritating effects: Corrosive! Damages skin and eyes.

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18
Version: 5.0

Page: 10/12
(30437532/SDS_GEN_CA/EN)

Information on: 2-heptanone

Assessment of irritating effects: Not irritating to the eyes. May cause slight irritation to the skin.

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Information on: Benzyl alcohol

Assessment of sensitization:

Animal studies and human data do not fully exclude a skin sensitizing potential.

Information on: ethylenediamine

Assessment of sensitization:

Caused skin sensitization in animal studies. The substance may cause sensitization of the respiratory tract.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

Information on: Benzyl alcohol

Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated ingestion of high doses.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity.

Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18
Version: 5.0

Page: 11/12
(30437532/SDS_GEN_CA/EN)

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Information on: n-butanol

Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

The potential to cause toxicity to development cannot be excluded when given in high doses.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

13. Disposal considerations

Waste disposal of substance:

Do not incinerate closed containers. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Do not discharge into drains/surface waters/groundwater.

Must be disposed of or incinerated in accordance with local regulations.

Container disposal:

Do not reuse containers without commercial reconditioning. WARNING: Empty containers may still contain hazardous residue.

14. Transport Information

Land transport

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT

Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3

Safety Data Sheet

LA20 EPOXY PRIMER ACTIVATOR

Revision date : 2022/03/18

Version: 5.0

Page: 12/12

(30437532/SDS_GEN_CA/EN)

Marine pollutant: NO
Proper shipping name: PAINT

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / listed

NFPA Hazard codes:

Health: 3 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2022/03/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET